## U.S. DEPARTMENT OF HOMELAND SECURITY Federal Emergency Management Agency National Flood Insurance Program

OMB No. 1660-0008 Expiration Date: November 30, 2022

# **ELEVATION CERTIFICATE**

Important: Follow the instructions on pages 1-9.

Copy all pages of this Elevation Certificate and all attachments for (1) community official, (2) insurance agent/company, and (3) building owner.

	SEC	TION A - PROPERT	Y INFOR	MATION		FOR INSU	JRANCE COMPANY USE
A1. Building Owne STEPHEN C. & M		EED				Policy Nu	mber:
A2. Building Stree Box No. 152 GAUSE DRIV		cluding Apt., Unit, Sui	te, and/o	or Bldg. No.) (	or P.O. Route an	Company	NAIC Number:
City VENICE				State Florida		ZIP Code 34293	
		and Block Numbers, Ta OT 11 & SOUTHWES					37150024
A4. Building Use (	e.g., Residei	ntial, Non-Residential,	Addition	, Accessory,	etc.) RESIDE	NTIAL	
		7.04322°					1927 X NAD 1983
A6. Attach at least	2 photograp	hs of the building if the	e Certific	ate is being i			
A7. Building Diagra							
A8. For a building	with a crawls	space or enclosure(s):					
a) Square foo	tage of craw	space or enclosure(s)			1509 sq ft		
b) Number of p	permanent flo	ood openings in the cr	awispac	e or enclosur	===== e(s) within 1.0 fo	ot above adjacent g	rade 13
c) Total net an	ea of flood o	penings in A8.b	1	1592 sq ir	1		
d) Engineered	flood openir	ngs? 🗓 Yes 🗌 N	10				
A9. For a building v	vith an attach	ned garage:					
a) Square foot				0 sqfl			
		pod openings in the at				diacont arodo. O	
		penings in A9.b	aonea g			djacent grade 0	
		gs? ☐ Yes ☒ N		0 sq	ın		
d) Liigiileeleu	noca openn	gs! ∐ Yes ⊠ N	10				
	SE	CTION B - FLOOD I	NSURA	NCE RATE	MAP (FIRM) IN	IFORMATION	
B1. NFIP Communi SARASOTA COUN				B2. County SARASOTA			B3. State Florida
B4. Map/Panel Number	B5. Suffix	B6. FIRM Index Date	Effe	RM Panel ective/	B8. Flood Zone(s)	B9. Base Flood I	Elevation(s) se Base Flood Depth)
12115C-0370	F	11-04-2016	11-04-2	vised Date 2016	AE	7'	
		Base Flood Elevation				ed in Item B9:	
☐ FIS Profile	<u>⊠</u> FIRM	Community Determined	nined [	☐ Other/Sou	rce:		
B11. Indicate eleva	tion datum u	sed for BFE in Item B	9: 🔲 N	GVD 1929 [	☑ NAVD 1988	Other/Source:	
B12. Is the building	located in a	Coastal Barrier Resor	urces Sy	stem (CBRS)	area or Otherw	ise Protected Area (	OPA)? ☐ Yes ☒ No
Designation D				☐ OPA			
EMA Form 096 0 22	******					···	

## **ELEVATION CERTIFICATE**

OMB No. 1660-0008 Expiration Date: November 30, 2022

IMPORTANT: In these spa	aces, copy the corresponding	information from Sec	tion A.	FOR IN	SURANC	E COMPANY USE
Building Street Address (in 152 GAUSE DRIVE	cluding Apt., Unit, Suite, and/or	Bldg. No.) or P.O. Rou	te and Box No.	Policy N	Number:	
City VENICE	State Flori		Code 93	Compar	ny NAIC N	Number
	SECTION C - BUILDING ELE	VATION INFORMAT	ION (SURVEY RE	QUIRE	D)	
C1. Building elevations a	re based on: Construction	n Drawings*	ding Under Constru	ction*	X  Finish	ned Construction
	rtificate will be required when co		-			
C2. Elevations – Zones A Complete Items C2.a Benchmark Utilized:	A1–A30, AE, AH, A (with BFE), \a–h below according to the build	/E, V1–V30, V (with BI ing diagram specified ing Vertical Datum:	n Item A7. In Puerto	AE, AR/A o Rico on	141–A30, A nly, enter r	AR/AH, AR/AO. meters.
	tum used for the elevations in ite					
The state of the s	9 NAVD 1988 Other/S	5 3	v.			
Annual to the second se	ing elevations must be the same		FE.			
-\ T(1 # 6		a s		000,00000000000000000000000000000000000		asurement used.
	or (including basement, crawlspa	ace, or enclosure floor)		202 20 2	× feet	meters
b) Top of the next hi					× feet	meters
	est horizontal structural member	(V Zones only)			× feet	meters
d) Attached garage	(top of slab)		***************************************	N/A	× feet	meters meters
e) Lowest elevation (Describe type of	of machinery or equipment servi equipment and location in Comr	cing the building nents)	-	4.0		meters
<ul><li>f) Lowest adjacent (</li></ul>	finished) grade next to building (	(LAG)		3.6	× feet	meters
g) Highest adjacent	(finished) grade next to building	(HAG)		3.9	× feet	meters
<ul> <li>h) Lowest adjacent g structural support</li> </ul>	grade at lowest elevation of deck	or stairs, including		3.6		meters
	SECTION D - SURVEYOR, I	ENGINEER, OR ARC	HITECT CERTIFIC	CATION		
This certification is to be s I certify that the informatio statement may be punished	igned and sealed by a land surv on on this Certificate represents in able by fine or imprisonment und	reyor, engineer, or arch my best efforts to interp der 18 U.S. Code, Sect	nitect authorized by oret the data availal ion 1001.	law to ce	ertify eleva lerstand th	ation information. hat any false
	de in Section A provided by a lice	ensed land surveyor?	⊠Yes □No	X C	heck here	if attachments.
Certifier's Name B. GREGORY RIETH		License Number 5228			CARCECE	J. 307
Title		5226		- 325	0.	7
PSM/CFM					Spr.	100
Company Name					0	ace) 10 =
STRAYER SURVEYING A	AND MAPPING, INC.			3.7	175	03119
Address 742 SHAMROCK BLVD				N	1	ěi <b>t</b>
City		State	ZIP Code	10	41	
VENICE		Florida	34293			
Signature	90	Date 03-20-2020	Telephone (941) 497-1290	Ext.		
Copy all pages of this Eleva	tion Certificate and all attachmen	ts for (1) community off	icial, (2) insurance a	gent/com	pany, and	(3) building owner.
FILE #20-03-25. THE WAT FROM A HAND HELD G.F CONVERTED FROM N.G. STRUCTURE HAS (13) FI SOLUTION VENTS; (11) N	of equipment and location, per (FER HEATER INSIDE OF THE FOR. UNIT (GPSTEST APP - NOW). V.D. 1929 DATUM TO N.A.V.D. LOOD VENTS, ENGINEERED FOR FOR SRE MODEL #FS1508-FOR. SR-3760. CERTIFICATE VALID	HOME WAS USED FO CONVERSION). ELEN 1988 DATUM USING FOR 1,592 SQUARE FOR HEX & (2) VENTS ARE	VATIONS SHOWN VERTCON CONVI EET (TOTAL). ALL MODEL #FS1616.	IN SECT ERSION (13) VEN . ATTACI	TION "C" \ PROGRA NTS ARE HED IS IC	WERE AM. SUBJECT FLOOD

the tell of the strains ંદ્રામાં મુકાઇએ ફાયા કર્યાં અને અને પ્રાથમ and produce that the second es surpret Bereigher and a section of APROFES gradient in a programment of the companies of the companies of or the of the Albertain Control to the control of the contro Budger Liberty er e gata, satem takatika 🗀 . Simple of the second of the second A STANDARD MANAGEMENT OF THE SECOND STANDARD STA water in the April rational to the control of the property of the second of Bargo - Louis Garant o Ligações e de elitaratuale do adding the line ing in the commence of the confidence of the con 1997 B. 14 Alaman and the state of the control of the second part of the second p ta in gradelije is en in te dice

respect of the collection of the

The state of the s

ka o jaman kata saga Pata Saga Sagara

A SWING CO.

## **ELEVATION CERTIFICATE**

OMB No. 1660-0008 Expiration Date: November 30, 2022

IMPORTANT: In these spaces, copy the correspondi	ng information from S	ection A.	FOR INSURANCE COMPANY USE
Building Street Address (including Apt., Unit, Suite, and 152 GAUSE DRIVE	or Bldg. No.) or P.O. Ro	oute and Box No.	Policy Number:
_ ·	tate ZI	P Code	Company NAIC Number
		293	
SECTION E – BUILDING ELI FOR ZONE	VATION INFORMATI AO AND ZONE A (W	ON (SURVEY NOT ITHOUT BFE)	REQUIRED)
For Zones AO and A (without BFE), complete Items E1-complete Sections A, B,and C. For Items E1-E4, use na enter meters.	-E5. If the Certificate is atural grade, if available	intended to support a . Check the measure	LOMA or LOMR-F request, ment used. In Puerto Rico only,
E1. Provide elevation information for the following and the highest adjacent grade (HAG) and the lowest a	check the appropriate be djacent grade (LAG).	oxes to show whethe	r the elevation is above or below
a) Top of bottom floor (including basement, crawlspace, or enclosure) is			s 🔲 above or 🦳 below the HAG.
<ul> <li>b) Top of bottom floor (including basement, crawlspace, or enclosure) is</li> </ul>			
E2. For Building Diagrams 6–9 with permanent flood op	enings provided in Sec	tion A Items 8 and/or	
the next higher floor (elevation C2.b in the diagrams) of the building is			<u>_</u>
E3. Attached garage (top of slab) is		feet meter	<del></del>
E4. Top of platform of machinery and/or equipment servicing the building is			
E5. Zone AO only: If no flood depth number is available	, is the top of the botton		cordance with the community's
floodplain management ordinance?	No Unknown. Th	e local official must o	pertify this information in Section G.
SECTION F - PROPERTY OWN	ER (OR OWNER'S RE	PRESENTATIVE) CE	RTIFICATION
The property owner or owner's authorized representative community-issued BFE) or Zone AO must sign here. The	who completes Sections statements in Sections	ns A, B, and E for Zons A, B, and E are cor	ne A (without a FEMA-issued or ect to the best of my knowledge.
Property Owner or Owner's Authorized Representative's	Name		
Address	City	Sta	ate ZIP Code
Signature	Date	Tel	ephone
Comments			
			Check here if attachments.

## **ELEVATION CERTIFICATE**

OMB No. 1660-0008 Expiration Date: November 30, 2022

IMPORTANT: In these spaces, copy the corresponding info		FOR INSURANCE COMPANY USE
Building Street Address (including Apt., Unit, Suite, and/or Bldo	g. No.) or P.O. Route and Box No	. Policy Number:
City State VENICE Florida	ZIP Code 34293	Company NAIC Number
SECTION G - COMMU	JNITY INFORMATION (OPTION	AL)
The local official who is authorized by law or ordinance to adm Sections A, B, C (or E), and G of this Elevation Certificate. Cor used in Items G8–G10. In Puerto Rico only, enter meters.	inister the community's floodplair mplete the applicable item(s) and	management ordinance can complete sign below. Check the measurement
G1. The information in Section C was taken from other de engineer, or architect who is authorized by law to cel data in the Comments area below.)	rtify elevation information. (Indica	te the source and date of the elevation
G2. A community official completed Section E for a building or Zone AO.	ing located in Zone A (without a F	EMA-issued or community-issued BFE)
G3. The following information (Items G4–G10) is provide	d for community floodplain mana	gement purposes.
G4. Permit Number G5. Date Pen	mit Issued G	Date Certificate of     Compliance/Occupancy Issued
G7. This permit has been issued for:	tion  Substantial Improvement	
G8. Elevation of as-built lowest floor (including basement) of the building:		feet  meters Datum
G9. BFE or (in Zone AO) depth of flooding at the building site:	:	feet  meters Datum
G10. Community's design flood elevation:		feet  meters Datum
Local Official's Name	Title	
Community Name	Telephone	
Signature	Date	
Comments (including type of equipment and location, per C2(e)	), if applicable)	
		☐ Check here if attachments.

## **BUILDING PHOTOGRAPHS**

### **ELEVATION CERTIFICATE**

See Instructions for Item A6.

OMB No. 1660-0008 Expiration Date: November 30, 2022

IMPORTANT: In these spaces, co	FOR INSURANCE COMPANY USE		
Building Street Address (including A 152 GAUSE DRIVE	apt., Unit, Suite, and/or Bldg. No.)	or P.O. Route and Box No.	Policy Number:
City VENICE	State Florida	ZIP Code 34293	Company NAIC Number

If using the Elevation Certificate to obtain NFIP flood insurance, affix at least 2 building photographs below according to the instructions for Item A6. Identify all photographs with date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View." When applicable, photographs must show the foundation with representative examples of the flood openings or vents, as indicated in Section A8. If submitting more photographs than will fit on this page, use the Continuation Page.



FRONT VIEW 03-20-2020

Photo One Caption

Clear Photo One



Photo Two Caption

Clear Photo Two

## **BUILDING PHOTOGRAPHS**

## **ELEVATION CERTIFICATE**

Continuation Page

OMB No. 1660-0008 Expiration Date: November 30, 2022

IMPORTANT: In these spaces, co	FOR INSURANCE COMPANY USE		
Building Street Address (including 152 GAUSE DRIVE	Policy Number:		
City	State	ZIP Code	Company NAIC Number
VENICE	Florida	34293	

If submitting more photographs than will fit on the preceding page, affix the additional photographs below. Identify all photographs with: date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View." When applicable, photographs must show the foundation with representative examples of the flood openings or vents, as indicated in Section A8.



VENTS 03-20-2020

Photo Three Caption

Clear Photo Three



VENTS 07-10-2020

Photo Four Caption

Clear Photo Four



# **ICC-ES Evaluation Report**

**ESR-3760** 

Reissued March 2020 Revised April 2020 This report is subject to renewal March 2022.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 08 00 00-OPENINGS

Section: 08 95 43-Vents/Foundation Flood Vents

REPORT HOLDER:

FLOOD SOLUTIONS, LLC

**EVALUATION SUBJECT:** 

STATIC FLOOD VENTS

#### 1.0 EVALUATION SCOPE

Compliance with the following codes:

- 2018, 2015, 2012 and 2009 International Building Code®
- 2018, 2015, 2012 and 2009 International Residential Code®

#### Property evaluated:

Water flow

#### 2.0 USES

Flood Solutions' static flood vents are used to provide for the equalization of hydrostatic flood forces on exterior walls.

#### 3.0 DESCRIPTION

#### 3.1 General:

Flood Solutions' static flood vents are engineered, permanently open flood vents with no moving parts that automatically allow flood waters to enter and exit enclosed areas. The vents are constructed of aluminum and available in four models. See Table 1 for model designations and sizes. See Figure 1 for illustrations of the flood vents.

#### 3.2 Engineered Opening:

The Flood Solutions static flood vents comply with the design principle noted in Section 2.6.2.2 of ASCE/SEI 24 for a rate of rise and fall of 5 feet per hour (0.423 mm/s). In order to comply with the engineered opening requirement of ASCE/SEI 24, the static flood vents must be installed in accordance with Section 4.0 of this report.

#### 3.3 Ventilation:

Flood Solutions' static flood vents may be used to supply natural ventilation for under-floor ventilation. See Table 1 for net free area for under-floor ventilation provided by each of Flood Solutions' static flood vents.

### 4.0 DESIGN AND INSTALLATION

The Flood Solutions static flood vents are designed to be installed into walls or doors of existing or new construction from the exterior side. Installation of the vents must be in accordance with the manufacturer's instructions, the

applicable code and this report. In order to comply with the engineered opening design principle noted in Section 2.6.2.2 of ASCE/SEI 24, the vents must be installed as follows:

- With a minimum of two opening on different sides of each enclosed area.
- With a minimum of one vent for the square footage of enclosed area noted in Table 1.
- Below the base flood elevation.
- With the bottom of the vent located a maximum of 12 inches (305 mm) above grade.

#### 5.0 CONDITIONS OF USE

The static flood vents described in this report comply with, or are a suitable alternative to what is specified in, those codes listed in Section 1.0 of this report, subject to the following conditions:

- 5.1 The static flood vents must be installed in accordance with this report, the applicable code and the manufacturer's installation instructions. In the event of a conflict, the instructions in this report govern.
- 5.2 The static flood vents must not be used in the place of "breakaway walls" in coastal high hazard areas, but are permitted for use in conjunction with breakaway walls in other areas.

### 6.0 EVIDENCE SUBMITTED

- 6.1 Manufacturer's descriptive literature and installation instructions.
- 6.2 Detail drawings.
- 6.3 Engineering calculations in accordance with ASCE/SEI 24.
- 6.4 Quality documentation in accordance with the ICC-ES Acceptance Criteria for Quality Documentation (AC10), dated June 2014.

#### 7.0 IDENTIFICATION

- 7.1 The Flood Solutions static flood vents recognized in this report must be identified by a label bearing the manufacturer's name (Flood Solutions), the model number, and the evaluation report number (ESR-3760).
- 7.2 The holder's contact information is the following:

FLOOD SOLUTIONS, LLC
ONE INDUSTRIAL PARK DRIVE
BUILDING 27
PELHAM, NEW HAMPSHIRE 03076
(800) 325-9775
www.floodsolutions.com
info@floodsolutions.com







TABLE 1—FLOOD SOLUTIONS STATIC FLOOD VENTS


MODEL	VENT SIZE (Width x Height) (in)	ROUGH OPENING SIZE (Width x Height) (in)	ENCLOSED AREA COVERAGE (ft²)	NET FREE AREA <sup>1</sup> (in²)
FS-1608	18 <sup>1</sup> / <sub>2</sub> x 10 <sup>1</sup> / <sub>2</sub>	16 x 8	97	80.7
FS-1616	18 <sup>1</sup> / <sub>2</sub> x 18 <sup>1</sup> / <sub>2</sub>	16 x 16	191	158.2
FS-1412	17 x 14 <sup>1</sup> / <sub>2</sub>	14 <sup>1</sup> / <sub>2</sub> x 12	129	106.7
FS-1608-Hex	18 <sup>1</sup> / <sub>2</sub> x 10 <sup>1</sup> / <sub>2</sub>	16 x 8	110	91.4

For SI: 1 inch = 25.4 mm; 1 ft = 304.8 mm


<sup>&</sup>lt;sup>1</sup>Available for use as under-floor ventilation.




FS-1412



FS-1608



FS-1616



FS-1608-HEX

FIGURE 1—FLOOD SOLUTIONS STATIC FLOOD VENTS



## **ICC-ES Evaluation Report**

# **ESR-3760 FBC and FRC Supplement**

Reissued March 2020 Revised April 2020 This report is subject to renewal March 2022.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 08 00 00—OPENINGS

Section: 08 95 43—Vents/Foundation Flood Vents

REPORT HOLDER:

FLOOD SOLUTIONS, LLC

**EVALUATION SUBJECT:** 

STATIC FLOOD VENTS

#### 1.0 REPORT PURPOSE AND SCOPE

#### Purpose:

The purpose of this evaluation report supplement is to indicate that Flood Solutions' flood vents, recognized in ICC-ES evaluation report ESR-3760, have also been evaluated for compliance with the codes noted below.

#### Applicable code editions:

- 2017 Florida Building Code—Building
- 2017 Florida Building Code—Residential

### 2.0 CONCLUSIONS

The Flood Solutions flood vents, described in Sections 2.0 through 7.0 of ICC-ES evaluation report <u>ESR-3760</u>, comply with the *Florida Building Code—Building* and the *Florida Building Code—Residential*, provided the design requirements are determined in accordance with the *Florida Building Code—Building* or the *Florida Building Code—Residential*, as applicable. The installation requirements noted in ICC-ES evaluation report ESR-3760 for the 2015 *International Building Code®* meet the requirements of the *Florida Building Code—Building* or the *Florida Building Code—Residential*, as applicable.

Use of the Flood Solutions' flood vents has also been found to be in compliance with the High-Velocity Hurricane Zone provisions of the Florida Building Code—Building and the Florida Building Code—Residential.

For products falling under Florida Rule 61G20-3, verification that the report holder's quality assurance program is audited by a quality assurance entity approved by the Florida Building Commission for the type of inspections being conducted is the responsibility of an approved validation entity (or the code official when the report holder does not possess an approval by the Commission).

This supplement expires concurrently with the evaluation report, reissued March 2020 and revised April 2020.

