493-4430

Florida

agen, should attach the original copy of the completed form to the flood insurance policy application,



FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ELEVATION CERTIFICATE

This form is to be used for: 1) New/Emergency Program construction in Special Flood Hazard Areas; 2) Pre-FIRM construction after September 30, 1982; 3) Post-FIRM construction; and, 4) Other buildings rated as Post-FIRM rules.

III DING OWNED			HERMI	1#B	ota.	of the
JILDING OWNER'S		-	ADDRESS		20	
Kirk Newman	TV					
Portion of	Lot 6, Sout			, Florida		
ertify that the information	on this certificate rep	resents my be	est efforts to interp	ret the data avail	able. I unde	rstand that any false
atement may be punishable CTION I ELIGIBILITY CI	ERTIFICATION (Con		cal Community Pe		Registered P	rofessional Engineer,
OMMUNITY NO PANEL NO. S	SUFFIX DATE OF FIRM	FIRM ZONE	DATE OF CONSTR	BASE FLOOD ELI		ig is
				D Pre-FIRM Re		☐ New/Emergency ☐ Pre-FIRM Reg ☐ Post-FIRM Reg.
ordinance. The co	the building describe ertifier may rely on co NGVD. Failure to co flood plain management	ommunity reconstruct the bu	ords. The lowest fl uilding at this elev	oor (including be	sement) wil	I be at an elevation
□ □ ordinance based	cribed above has been on elevation data and attach copy of varian	d visual inspec	ction or other reas	h the community onable means.	's flood plai	n management
ES NO The mobile home	located at the address d plain management	ss described of	above has been tie	d down (anchore	ed) in compl	iance with the
MOBILE HOME MAKE			OF MANUFACTU		IAL NO.	DIMENSIONS
10						
Community Permit Official	or Registered Profess	ional Enginee	er, Architect, or Su	rveyor)		
IAME			ADDRESS	-	7	
	125					710
ITLE	CITY			STATE		ZIP
an e	tify that the building an elevation of +15.	0_feet, NGVD	y location describe GVD (mean sea lev D. 2 Stor	y frame &	CBS	the building site is a
	I certify that the buildi at an elevation of is at an elevation of	feet	perly location desc t, NGVD (mean se et, NGVD.	ribed above has to a level), and the	he bottom of average gra	the lowest floor bean de at the building sit
FIRM ZONES A, A99, AH and	EMERGENCY PROC	RAM: Leertify	The later of the same of the			
loor elevation of	feet, NGVD. The el	evation of the	that the building a highest adjacent g	t the property loca rade next to the b	ation describ uilding is	ed above has the lowe
lioor elevation of	at the building at the	property loca	highest adjacent g	ove has the lowes	uilaing is	teet, NGV
FIRM ZONE AO: I certify the feet, NGVD. The elevation of	at the building at the of the highest adjacen	property loca t grade next t	highest adjacent g ation described abo the building is_	ove has the lowes	at floor elevent, NGVD.	tion of
FIRM ZONE AO: I certify the feet, NGVD. The elevation of SECTION III FLOODPRO I certify to the best of my walls substantially imperme and hydrodynamic loads at forces associated with the best of my walls substantially imperme and hydrodynamic loads at forces associated with the best of my walls substantially imperme and hydrodynamic loads at forces associated with the best of my walls substantially impermediate.	at the building at the of the highest adjacen OFING CERTIFICAT knowledge, informaticable to the passage ad effects of buoyanchase flood.	property loca t grade next t ION (Certification, and belief of water and by that would	thighest adjacent gation described about the building is attempting the building is attempting that the building structural compose caused by the	red Professional E is designed so the theorem is designed to the theorem is the t	at floor elevant, NGVD. Engineer or a capability of a sures velocity.	Architect) Along is watertight, winder tesisting hydrostatities, impact and upl
FIRM ZONE AO: I certify the leet, NGVD. The elevation of SECTION III FLOODPRODICE CERTIFY to the best of my walls substantially imperment and hydrodynamic loads at forces associated with the backet of the current of	at the building at the of the highest adjacent of the highest adjacent of the highest adjacent case flood. The event of flooding, with the times measures are unless measures are ors and windows).	properly local tigrade next tig	thighest adjacent gation described about the building is ation by a Register at the building ation at the flood by a Register at the building will enter the building at the flood to prevent	red Professional E is designed so the sharing the flood depths, pre be achieved with ding when floods	st floor elevat, NGVD. Engineer or that the built capability capability of the built up to the buy	Architect) Architect) Ing is watertight, winderesisting hydrostate ities, impact and uplear vention? Invention?
FIRM ZONE AO: I certify the leet, NGVD. The elevation of SECTION III FLOODPROFILE of the leet of leet of leet of the leet of l	at the building at the of the highest adjacent of the highest adjacent of the highest adjacent of the passage in the passage of the passage of the passage flood, the event of flooding, the auniess measures are unless measures are ors and windows). If the building be occupions is YES, the flooding the passage of the pass	property loca t grade next t ION (Certification, and belief of water and ty that would will this degree ans that water taken prior to upled as a resi	thighest adjacent gation described about the building is— ation by a Register that the building structural compose caused by the se of floodproofing will enter the building the flood to prevent the	red Professional E is designed so the flood depths, pre be achieved with ding when floods ent entry of water	st floor elevation of the build capability capability of the build capability	Architect) Sing is watertight, with fresisting hydrostate ities, impact and uple ervention? ase flood level ocag metal shields over
FIRM ZONE AO: I certify the leet, NGVD. The elevation of SECTION III FLOODPRO I certify to the best of my walls substantially imperment and hydrodynamic loads at forces associated with the term of the least of th	at the building at the of the highest adjacent of the highest adjacent of the highest adjacent of the highest adjacent of the passage of the highest adjacent of the highest of the highes	property loca t grade next t ION (Certification, and belief of water and ty that would will this degree ans that water taken prior to upled as a resi	ation described about the building is ation by a Register at the building structural compose caused by the see of floodproofing will enter the building the flood to prevent at the building ation at the credited for and floodproofing	red Professional E is designed so the flood depths, pre be achieved with ding when floods ent entry of water	st floor elevat, NGVD. Engineer or shat the build capability capability capability to the build up to the build (e.g., boiting and the actument of the actument of the build (e.g., boiting and the actument of the actument of the actument of the a	Architect) ding is watertight, winder resisting hydrostaticities, impact and uplear vention? asse flood level ocage metal shields over all lowest floor must be
FIRM ZONE AO: I certify the leet, NGVD. The elevation of SECTION III FLOODPRODUCE. It certify to the best of my walls substantially imperment and hydrodynamic loads are forces associated with the back yes. NO In the Curricular in the least of the control of the least of the lea	at the building at the of the highest adjacen. OFING CERTIFICAT: knowledge, informatic acable to the passage of effects of buoyance acase flood. The event of flooding, man intervention measures are unless measures are unless measures are to sand windows). If the building be occurred to the building be occurred to the floodite ad. Complete both 1/1-V30, AO and AH;	property loca t grade next t ION (Certification, and belief of water and ty that would will this degree ans that water taken prior to upled as a resi proofing cannot the elevation a	ation described about the building is ation by a Register at the building structural compose caused by the see of floodproofing will enter the building the flood to prevent at the building ation at the credited for and floodproofing	red Professional E is designed so the flood depths, pre be achieved with ding when floods ent entry of water rating purposes a certificates.	st floor elevat, NGVD. Engineer or shat the build capability capability capability to the build up to the build (e.g., boiting and the actument of the actument of the build (e.g., boiting and the actument of the actument of the actument of the a	Architect) ding is watertight, winder resisting hydrostaticities, impact and uplear vention? asse flood level ocage metal shields over all lowest floor must be
FIRM ZONE AO: I certify the feet, NGVD. The elevation of SECTION III FLOODPRO I certify to the best of my walls substantially imperment and hydrodynamic loads at forces associated with the base of the control of the	at the building at the of the highest adjacen. OFING CERTIFICAT: knowledge, informatic acable to the passage of effects of buoyance acase flood. The event of flooding, man intervention measures are unless measures are unless measures are to sand windows). If the building be occurred to the building be occurred to the floodite ad. Complete both 1/1-V30, AO and AH;	property loca t grade next t ION (Certifica on, and belief of water and by that would will this degre ans that water taken prior to pied as a resi proofing cannot be elevation a BOTH SE COMPAN	thighest adjacent gotton described about the building is attion by a Register attion by the flood proofing will enter the built the flood to prevent at the flood to prevent attion at the flood proofing and floodproofing attitude attions at the flood proofing attitude	red Professional E is designed so the nents having the flood depths, pre be achieved with ding when floods ent entry of water raling purposes a certificates.	st floor elevation is	Architect) ding is watertight, winder resisting hydrostaticities, impact and uplear vention? asse flood level ocag metal shields over all lowest floor must be
FIRM ZONE AO: I certify th feet, NGVD. The elevation of SECTION III FLOODPRODE I certify to the best of my walls substantially imperme and hydrodynamic loads at forces associated with the by YES NO In the Curry door YES NO Will If the answer to both questicompleted and certified ins FIRM ZONES A, A1,-A30, V	at the building at the of the highest adjacent of the highest adjacent of the highest adjacent of the passage in the passage of the passage flood, the event of flooding, the event of flooding the event of floo	property loca t grade next t ION (Certifica on, and belief of water and by that would will this degre ans that water taken prior to pied as a resi proofing cannot be elevation a BOTH SE COMPAN	ation described aboot the building is ation by a Register at a the building structural compose caused by the ation of the caused by the ation of the flood to prevent and floodproofing at the flood proofing at the flood proofing at the flood proofing at the floodproofing at the floodproo	red Professional E is designed so the nents having the flood depths, pre be achieved with ding when floods ent entry of water raling purposes a certificates.	st floor elevation is	Architect) Sing is watertight, will resisting hydrostal cities, impact and uple revention? ase flood level ocgretal shields over all lowest floor must

-8/19/87 Venice,