FEDERAL EMERGENCY MANAGEMENT AGENCY

OMB 3067-0077



ELEVATION CERTIFICATE

This form is to be used for: 1) New/Emergency Program construction in Special Flood Hazard Areas; 2) Pre-FIRM construction after September 30, 1982; 3) Post-FIRM construction; and, 4) Other buildings rated as Post-FIRM rules.

obert Hamilton	24:					orida 33595
DING OWNER'S			DDRESS		100	
ot 5, Block 47,	"CORRECTED	PLAT O	F BAY POI	NT SUI	3."	
PERTY LOCATION (Lot an	d Block numbers and	address if a	available)	2000	HRS	10017/10
				erm	17 4 00	contand that any false
att that the information or	this certificate repres	sents my bes	st efforts to interp	oret the dat n 1001.	a available. I unde	erstand that diff idea
rtify that the information or ement may be punishable b CTION I ELIGIBILITY CER	TIFICATION (Comp	leted by Loca	al Community Pe	rmit Officia	l or a Registered P	Professional Engineer,
TION I ELIGIBILITY OF	Archite				OOD ELEV. BUILDI	
MMUNITY NO. PANEL NO. SU	FFIX DATE OF FIRM	FIRM ZONE	DATE OF CONSTR.	(In AO Zon	e, use depth)	□ New/Emergency - □ Pre-FIRM Reg.
				1		□ Post-FIRM Reg
offt, I	the building described tifier may rely on com NGVD. Failure to con- ood plain managemen	struct the bu	uilding at this elev	vation may	place the building	In violation of
ES- NO The building descri	ribed above has been	constructed	in compliance w ction or other rea	ith the com sonable me	munity's flood pla eans.	ain management
If NO is checked,	attach copy of variant	ce issued by	the community.	ad down (anchored) in com	pliance with the
Community's floor	plain management				SERIAL NO.	DIMENSIONS
MOBILE HOME MAKE	MODEL	YR.	OF MANUFACT	UNE		X
# St 2	04			-	=======================================	
Community Permit Official	or Registered Professi	onal Engine	er, Architect, or S	Surveyor)	100000000000000000000000000000000000000	
Community Permit Cimerary	, riegiotei e		ADDRESS			
NAME				F F (2)	22 7	ZIP
TITLE	CITY			STA	(TE	4-11
-					ter second	
			DATE		PHONE	
SECTION II ELEVATION FIRM ZONE A1-A30: I cer	1500	ertified by a L chitect, or Su		Permit Off	hab the lowest liche average grade	of (including basement) at the building site is at
FIRM ZONE A1-A30: 1 cer at a an e	tify that the building in elevation of +16.	ertified by a Lehitect, or Su at the proper 5_feet, Nov	Local Community urveyor.) rty location descr IGVD (mean sea /D.	Permit Off ribed above level) and t (2nd s	habithas the lowest liche average grade	at the building site is at table)
FIRM ZONE A1-A30: I cer at ai an e	rify that the building an elevation of +16 elevation of +4.5 I certify that the building at an elevation of is at an elevation of _	ertified by a L chitect, or Su at the proper 5 feet, NGV ing at the pro	Local Community urveyor.) rty location description de	Permit Off ribed above level) and t (2nd s escribed ab- sea level),	habithas the lowest to habit he average government to habitour habitour habitour habitour habithas the bottom and the average government habithas the bottom and the average government habithas the habithas habi	or (including basement) or at the building site is at table) n of the lowest floor beam grade at the building site
FIRM ZONES V, V1-V30:	rify that the building in elevation of +1.6. elevation of +4.5. I certify that the build at an elevation of is at an elevation of is at an elevation of defended the elevatio	ertified by a L chitect, or Su at the proper 5 feet, N feet, NGV ing at the pro- feet	Local Community urveyor.) rty location description de	ribed above level) and to (2nd sescribed absea level),	has the lower the average of the ave	or (including basement) e at the building site is at table) n of the lowest floor beam grade at the building site cribed above has the lowest feet, NGVI
FIRM ZONE A1-A30: I cer at a an e FIRM ZONES V, V1-V30: FIRM ZONES A, A99, AH an allow elevation of	rify that the building in elevation of +16. Elevation of +4.5 I certify that the build at an elevation of is at an elevation of elet, NGVD. The elet the building at the of the highest adjacer.	entified by a L chitect, or Su at the proper 5 feet, N feet, NGV ing at the pro fer GRAM: I certi levation of the property loon t grade next	Local Community preyor.) rty location described for the building in the building it to the building it to the building it.	Permit Office above level) and to (2nd secribed above has is	has the lowes the average grade tory habitove has the bottom and the average grade perty location description described by the lowest floor elect, NGVD.	cor (including basement) at the building site is at table) n of the lowest floor beam grade at the building site cribed above has the lowe- feet, NGVI
FIRM ZONES V, V1-V30: FIRM ZONES A, A99, AH an aloor elevation of Get, NGVD. The elevation	rify that the building in elevation of +16. elevation of +4.5 I certify that the building at an elevation of is at an elevation of elect, NGVD. The elevation of the highest adjacer	ertified by a L thitect, or Su at the proper 5 feet, N feet, NGV ing at the pro tertification of the property look to grade next	Local Community urveyor.) rty location description of the community location description described to the building in the bui	Permit Off ribed above level) and t (2nd secribed above sea level), gat the pro- nt grade ner above has secribed Profi	has the lowest to the building is the lowest floor effect, NGVD.	cribed above has the lower feet, NGVI
FIRM ZONE A1-A30: I cer at an an e FIRM ZONES V, V1-V30: FIRM ZONES A, A99, AH an alloor elevation of FIRM ZONE AO: I certify the at, NGVD. The elevation SECTION III FLOODPRO Received to the best of my walls substantially imperment hydrodynamic loads of torces associated with the YES INO In In (He)	rify that the building in elevation of +16. elevation of +16. Elevation of +16. It certify that the building at an elevation of is at an elevation of is at an elevation of elect, NGVD. The elect, NGVD. The elevation of the highest adjacer. **DOFING CERTIFICAT** **Anowledge, informat meable to the passage and effects of buoyan is base flood.** **The event of floodings.** **Author of floodings.** **Long the passage and effects of buoyan intervention means are unless measures are are all the passage.**	entified by a L chitect, or Su at the proper 5 feet, N' feet, NGV ing at the pro fer GRAM: I certification of the property loon t grade next FION (Certification, and belies of water ar cy that woul will this deci	Local Community uneyor.) rty location described to the building into the building i	Permit Off ribed above level) and to (2nd second above has sea level), above has stered Profiting is designated above has inponents hither flood defing be ach	has the lowes flot to the building is the lowest floor elect, NGVD. essional Engineer gned so that the bave has the bottom and the average of the building is the lowest floor elect, NGVD.	or (including basement) at the building site is at table) of the lowest floor beam grade at the building site cribed above has the lowes feet, NGVI levation of or Architect) building is watertight, with ity of resisting hydrostat relocities, impact and upli
FIRM ZONE A1-A30: I cert at at a an element of the second	rify that the building in elevation of +16. elevation of elevation elevation of elevation eleva	at the proper 5 feet, N feet, NGV fe	Local Community urveyor.) rty location description of the community location described to the building of the community of t	Permit Off ribed above level) and to (2nd secribed above sea level), g at the pro above has is stered Profitting is desirated inponents he the flood do fing be ach building wherevent enter	has the lowestic the average grade tory habitone has the bottom and the average grade to the building is the lowest floor elect, NGVD. essional Engineer grade so that the baving the capability of water (e.g., bottom of water and the purposes and the	cribed above has the lower feet, NGVI levation of or Architect) building is watertight, with the following side is at the building side is feet, NGVI levation of or Architect) building is watertight, with the following is watertight, with the feet is side in the feet in the feet is side in the feet in the feet in the feet is side in the feet in the f
FIRM ZONE A1-A30: I cert at at an experience of the state	rify that the building in elevation of +16. elevation of elevation of is at an elevation of elevation elevation of elevation el	at the proper 5 feet, N feet, NGV fe	Local Community urveyor.) rty location descrigVD (mean sea I/D. operty location det, NGVD (mean feet, NGVD. iffy that the building in the highest adjacer cation described to the building in the fighest adjacer cation by a Region described to the building in the fighest adjacer cation by a Region of the fight of t	Permit Off ribed above level) and to (2nd sees ribed above has seed level), gat the property above has seed level	has the lowestic the average grade tory habitone has the bottom and the average grade to the building is the lowest floor elect, NGVD. essional Engineer grade so that the baving the capability of water (e.g., bottom of water and the purposes and the	or (including basement) at the building site is at table) n of the lowest floor beam grade at the building site cribed above has the lower feet, NGVI levation of or Architect) building is watertight, with ity of resisting hydrostat relocities, impact and upli- intervention? ne base flood level oc- olting metal shields over actual lowest floor must
FIRM ZONES A, A99, AH and an elevation of the second and the secon	riffy that the building in elevation of +16. Hevation of -16. Hevation of -17. Hevation of -18. Hevation of	at the proper 5 feet, N feet, NGV fe	Local Community urveyor.) rty location described for the highest adjacer cation described to the building in the highest adjacer cation described to the building in the highest adjacer cation described to the building in the highest adjacer cation described to the building in the building in the building in the caused by gree of floodprooter will enter the to the flood to presidence? annot be credited on and floodproof	Permit Off ribed above level) and to (2nd secribed ab- sea level), gat the pro- nt grade ner above has is stered Prof- ting is desir hen flood ach building wh revent entir to for rating ting certific tified Flood	has the lowes fine average grade story habitone has the bottom and the average grade at to the building is the lowest floor elect, NGVD. essional Engineer grade so that the baving the capability of water (e.g., because of the building is the lowest floor elect, NGVD.	or (including basement) at the building site is at table) n of the lowest floor beam grade at the building site cribed above has the lower feet, NGVI levation of or Architect) building is watertight, with ity of resisting hydrostat relocities, impact and upli- intervention? ne base flood level oc- olting metal shields over actual lowest floor must
FIRM ZONE A1-A30: I cert at at an experience of the state	riffy that the building in elevation of +16. Hevation of -16. Hevation of -17. Hevation of -18. Hevation of	at the proper 5 feet, N feet, NGV fe	Local Community urveyor.) rty location descrigVD (mean sea I/D. operty location det, NGVD (mean feet, NGVD. iffy that the building to the highest adjacer cation described to the building in the highest adjacer cation described to the building in the feet of the flood proof the residence? annot be credited on and floodproof cert if SECTIONS II All SECTIONS III Al	Permit Off ribed above level) and to (2nd secribed ab- sea level), gat the pro- nt grade ner above has is stered Prof- ting is desir hen flood ach building wh revent entir to for rating ting certific tified Flood	has the lowes the lowes the lowes the lowes the lowes the lowes to the bottom and the average of the lowest floor elect, NGVD. essional Engineer great to the building is the lowest floor elect, NGVD. essional Engineer great to the baving the capabilitie piths, pressures vieved with human en floods up to the form of water (e.g., but purposes and the lates.	or (including basement) at the building site is at table) n of the lowest floor beam grade at the building site cribed above has the lower feet, NGVI levation of or Architect) building is watertight, with ity of resisting hydrostat relocities, impact and upli- intervention? ne base flood level oc- olting metal shields over actual lowest floor must
FIRM ZONES V, V1-V30: FIRM ZONES V, V1-V30: FIRM ZONES A, A99, AH and an elevation of the control of the cont	rify that the building in elevation of +16. elevation of elevation of is at an elevation of is at an elevation of elect, NGVD. The elevation ele	entified by a Lichitect, or Surat the property feet, Noving at the property feet, Noving and belief of water are cythat would will this degree and that water taken prior suppled as a middroofling can the elevation.	Local Community urveyor.) rty location description of the community of th	Permit Off ribed above level) and to (2nd secribed above sea level), g at the pro- nt grade ner above has is stered Profi ling is designated above the flood do fing be ach building wh revent entre if or rating fing certific tified Flood ND III (Che	has the lowes file tory habithe average grades tory habithe average grades tory habithe average grades to the building is the lowest floor elect, NGVD. The sessional Engineer grades that the baving the capability of water (e.g., but yof water (e.g., but yof water (e.g., but purposes and the ates. The proofed Elevation ck One)	cor (including basement) at the building site is at table) n of the lowest floor beam grade at the building site cribed above has the lowest feet, NGVE levation of or Architect) building is watertight, wit ity of resisting hydrostat velocities, impact and upli intervention? he base flood level oc- olting metal shields over actual lowest floor must isfeet, (NGVE)
FIRM ZONES V, V1-V30: FIRM ZONES V, V1-V30: FIRM ZONES A, A99, AH and all and all and all all all all all all all all all al	rify that the building in elevation of +16. elevation of elevation of is at an elevation of is at an elevation of elect, NGVD. The elevation ele	entified by a Lehitect, or Suat the properson of the prop	Local Community urveyor.) rty location described for the highest adjacer cation described to the building in the highest adjacer cation described to the building in the highest adjacer cation described to the building in the highest adjacer cation described to the building in the building in the building in the caused by a Region of the caused by the flood to prove the flood to presidence? annot be credited on and floodproof credited on and floodproof cert in the flood to presidence? A SECTIONS II ALPANY NAME B ISCAYING	Permit Off ribed above level) and to (2nd secribed above sea level), g at the pro- nt grade ner above has is stered Profi ling is designated above the flood do fing be ach building wh revent entre if or rating fing certific tified Flood ND III (Che	has the lowes file tory habithe average grades tory habithe average grades tory habithe average grades to the building is the lowest floor elect, NGVD. The sessional Engineer grades that the baving the capability of water (e.g., but yof water (e.g., but yof water (e.g., but purposes and the ates. The proofed Elevation ck One)	or (including basement) at the building site is at table) of the lowest floor beam grade at the building site cribed above has the lower feet, NGVI levation of or Architect) building is watertight, with ity of resisting hydrostat relocities, impact and upli intervention? he base flood level oc- olting metal shields over actual lowest floor must isfeet, (NGVI CENSE NO. (or Affix Sea
FIRM ZONES V, V1-V30: FIRM ZONES V, V1-V30: FIRM ZONES A, A99, AH and an elevation of the control of the cont	rify that the building in elevation of +16. elevation of elevation of is at an elevation of is at an elevation of elect, NGVD. The elevation ele	at the proper 5 feet, N feet, NGV fe	ry location described for the building in the	Permit Off ribed above level) and to (2nd secribed ab- sea level), gat the pro- above has is stered Prof- ting is desirated the flood ach building wh revent entire to for rating ting certific tified Flood ND III (Che	has the lowes the lowes the average grade story habitove has the bottom and the average grade to the building is the lowest floor elect, NGVD. essional Engineer grade so that the baving the capabilitiepths, pressures viewed with human ten floods up to the yof water (e.g., bottom purposes and the ates. proofed Elevation ck One)	cribed above has the lower feet, NGVI levation of resisting hydrostative locities, impact and uplications metal lowest floor must feet, NGVI levation of resisting hydrostative locities, impact and uplications metal shields over actual lowest floor must feet, NGVI levation?
FIRM ZONES V, V1-V30: FIRM ZONES V, V1-V30: FIRM ZONES A, A99, AH an allow of elevation of the properties of the prope	rify that the building in elevation of ±16. Hevation in the event of flooding, turnal intervention metals measures are cors and windows). He building be occurred to the building be occurred to the passage and effects of buoyan the event of flooding, turnal intervention metals measures are cors and windows). He building be occurred to the building be	at the proper, 5 feet, N feet, NGV f	ry location described for the building in the	Permit Off ribed above level) and to (2nd secribed ab- sea level), gat the pro- above has is stered Prof- ting is desirated the flood ach building wh revent entire to for rating ting certific tified Flood ND III (Che	has the lowes the lowes the average grade story habitove has the bottom and the average grade to the building is the lowest floor elect, NGVD. essional Engineer grade so that the baving the capabilitiepths, pressures viewed with human ten floods up to the yof water (e.g., bottom purposes and the ates. proofed Elevation ck One)	cribed above has the lower feet, NGVE levation of cor Architect) building is watertight, with the position of resisting hydrostate velocities, impact and uplicating metal shields over actual lowest floor must feet, NGVE levation of cor Architect) building is watertight, with the position of cor Architect provided intervention? The base flood level occolting metal shields over actual lowest floor must feet, (NGVE) CENSE NO. (or Affix Sea 2009
FIRM ZONES V, V1-V30: FIRM ZONES V, V1-V30: FIRM ZONES A, A99, AH an aloor elevation of the property of the period of the property of the property of the period of the property of the period of the period of the property of the period o	rify that the building in elevation of ±16. elevation	artified by a L chitect, or Su at the proper 5 feet, N feet, NGV ing at the pro feet, NGV ing at	Local Community urveyor.) rty location descrigVD (mean sea I/D. operty location deet, NGVD (mean feet, NGVD. iffy that the building in the highest adjacer cation described at to the building in the highest adjacer cation described in the building in the highest adjacer cation described at to the building in the building in the cation by a Region in the caused by gree of floodproof the caused by gree of floodproof the flood to presidence? annot be credited on and floodproof in SECTIONS II APANY NAME e Biscayneress e Biscayneress nter Cour	Permit Off ribed above level) and to (2nd second above has sea level), gat the property of the second grade new above has second grade new above has second from the flood do fing be ach building wherevent entered from the flood of the second from the flood of the second from the flood of th	has the lowes the lowes floor exerged grade story habitove has the bottom and the average of the lowest floor exercised by the lowest floor exercised with human ten floods up to the lowest floor exercised with human ten floor exercised with	cor (including basement) at the building site is at table) n of the lowest floor beam grade at the building site cribed above has the lowest feet, NGVE levation of or Architect) building is watertight, wit ity of resisting hydrostat relocities, impact and upli intervention? he base flood level oc- olting metal shields over actual lowest floor must isfeet, (NGVE) ICENSE NO. (or Affix Sea

INSURANCE AGENTS MAY ORDER THIS FORM

04 94 EED 03

REPLACES FEMA FORM 81-31, APR 62, WHICH IS OBSOLETE.