p. 3

Mar 20 00 09:27a

Van Buskirk Engineering 941-426-6101

1

p. 1

Expires May 31, 1996

Bup 2000 -024

ELEVATION CERTIFICATE

FEDERAL EMERGENCY MANAGEMENT AGENCY

NATIONAL FLOOD INSURANCE PROGRAM

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR).

Instructions for completing this form can be found on the following pages. FOR INSURANCE COMPANY USE SECTION A PROPERTY INFORMATION POLICY NUMBER BUILDING OWNER'S NAME Ron Spector COMPANY NAIC NUMBER STREET ADDRESS (Including Apt., Unit. Suite and/or Bidg. Number) or P.O. ROUTE AND BOX NUMBER 220 Natures Way OTHER DESCRIPTION it of and Block Numbers, etc.) Lot 207, Riverwalk Mobile Home Village Zip Code STATE 34287 Florida Venice SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION Provide the following from the proper FIRM (See instructions): 6.BASEFLOOD ELEVATION 4. DATE OF FIRM INDEX 3.SUFFIX 2.PANEL NUMBER (m AO Zones, use deprin) I COMMUNITY NUMBER - - 8ft. A8 D 09-03-92 0375 125144 Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): x NGVD'29 Other (describe on back). For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the feet NGVD (or other FIRM detum - see Section B, Item 7). 8. community's BFE: SECTION C BUILDING ELEVATION INFORMATION Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pogos 5 and 6 that best describes the subject building's reference level 5 FIRM Zones A1 - A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of 2.(a) 9.4 teet NGVD (or other FIRM datum-sea Section B, Item 7) FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of ______ foot NGVD (or other FIRM datum-see Section B, Item 7). (b) FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is (c) (check one) the highest grade adjacent to the building. feet above □ or below □ (check one) the FIRM Zone AO. The floor used as the reference level from the selected diagram is _ highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in (d) accordance with the community's floodplain management ordinance?

Yes

No

Unknown Indicate the elevation datum system used in determining the above reference elevations: x NGVD'29 D Other (describe under Comments on Page 2) (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM (see Section 8, Item 7), 3. then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.) Elevation reference mark used appears on FIRM: Tes x No (See Instructions on Page 4) The reference level elevation is based on: x actual construction construction drawings 4. (Note: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this 5 certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.) The elevation of the lowest grade immediately adjacent to the building is 7.0 feet NGVD (or other FIRM datum - see Section 6 B, Item 7). SECTION D COMMUNITY INFORMATION 1.If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is not the "lowest floor" as defined in the community's flood plain management ordinance, the elevation of the building's "lowest floor" as defined by the feet NGVD (or other FIRM datum-see Section B, Item 7).

Date of the start of construction or substantial improvement

p. 2

p. 2

Van Buskirk Engineering

941-426-6101

Mar 20 00 09:27a


SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1-A30, AE, AH, A (with BFE),V1-V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community Issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features-If the certifler is unable to certify to breakaway/non breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unlinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

Alan K. Fish	Florida P.S.M. # 3941		
Registered Professional	Surveyor & Mapper	A. L. Van Bus Planners, Inc	skirk Engineers &
ADDRESS 12450-D Tamiami Trail	North Port		Florida 34287
SIGNATURE MEAN TON	3-	DATE 17-00 (941) PHOP	¥426-0681
Copies should be made of this Certificate COMMENTS:	, committee, at make	naixe againcompany, a	ind 37 building owner.



The diagrams above Illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.