ELEVATION CERTIFICATE

IMPORTANT: Follow the instructions on pages 1-9.

OMB No. 1660-0008 Expiration Date: July 31, 2015

SEC'	FION F	FOR INSURANCE COMPANY USE					
A1. Building Owner's Name Vernon Stein		Policy Number:					
A2. Building Street Address (including Apt., Unit, Suite, and 910 Neptune Drive		Company NAIC Number:					
City Englewood	ZIF	ZIP Code 34223					
A3. Property Description (Lot and Block Numbers, Tax Parc Lot 338, Overbrook Gardens Section No. 3		,					
 A4. Building Use (e.g., Residential, Non-Residential, Addition A5. Latitude/Longitude: Lat. <u>N 27,00070</u> A6. Attach at least 2 photographs of the building if the Cere A7. Building Diagram Number <u>1B</u> 	Long. w 82.389	900	Horizontal Da	atum: 🗌 NAD 1927 🔀 NAD 1983			
 A8. For a building with a crawlspace or enclosure(s): a) Square footage of crawlspace or enclosure(s) b) Number of permanent flood openings in the crawlsp or enclosure(s) within 1.0 foot above adjacent grade c) Total net area of flood openings in A8.b d) Engineered flood openings? Yes No 	e 50	qft a)S b)N w qin c)To	ithin 1.0 foot above a otal net area of flood of	ched garage 711 sq ft flood openings in the attached garage djacent grade 14 openings in A9.b 711 sq in			
d) Engineered flood openings? ☐ Yes ☐ No SECTION B – FLOOD INSURANCE RATE MAP (FIRM) INFORMATION							
B1. NFIP Community Name & Community Number	B2. County	international and a second	INFORMATION				
Sarasota County & 125144	Sarasota			B3. State FL			
B4. Map/Panel Number B5. Suffix B6. FIRM Index 0344/ 125144 E 09/03/19	Revise	Panel Effective/ d Date 03/1992	B8. Flood Zone(s)	B9. Base Flood Elevation(s) (Zone A0, use base flood depth) 12.0 feet			
B10. Indicate the source of the Base Flood Elevation (BFE) d ☐ FIS Profile							
B11. Indicate elevation datum used for BFE in Item B9: ☑ NGVD 1929 □ NAVD 1988 □ Other/Source: B12. Is the building located in a Coastal Barrier Resources System (CBRS) area or Otherwise Protected Area (OPA)? □ Yes ☑ No Designation Date: / □ CBRS □ OPA SECTION C – BUILDING ELEVATION INFORMATION (SURVEY REQUIRED)							
C1. Building elevations are based on: Construction Drawings* Building Under Construction* X Finished Construction * A new Elevation Certificate will be required when construction of the building is complete.							
	Drawings*	Building Under C					
 *A new Elevation Certificate will be required when const C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V2 C2.a–h below according to the building diagram specifie 	truction of the buildin L–V30, V (with BFE), A ed in Item A7. In Puer	ng is complete. AR, AR/A, AR/AE, to Rico only, ente	AR/A1-A30, AR/AH, er meters.	Finished Construction			
 *A new Elevation Certificate will be required when const C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V1 C2.a–h below according to the building diagram specific Benchmark Utilized: Sarasota County BM 485 B 	truction of the buildin L–V30, V (with BFE), A ed in Item A7. In Puer Ver	ng is complete. AR, AR/A, AR/AE, to Rico only, ente rtical Datum: <u>NG</u>	AR/A1-A30, AR/AH, ar meters. GVD 1929 Ele	Finished Construction AR/AO. Complete Items vation = 10.928 feet			
 *A new Elevation Certificate will be required when const C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V2 C2.a–h below according to the building diagram specifie 	truction of the buildin L–V30, V (with BFE), A ed in Item A7. In Puer ————Ver us a) through h) below	ng is complete. AR, AR/A, AR/AE, to Rico only, ente rtical Datum: <u>NG</u> v. X NGVD 1925	AR/A1-A30, AR/AH, ar meters. BVD 1929 Ele 9 🗌 NAVD 1988 🗌	Finished Construction AR/AO. Complete Items vation = 10.928 feet Other/Source:			
 *A new Elevation Certificate will be required when const C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V2 C2.a–h below according to the building diagram specific Benchmark Utilized: Sarasota County BM 485 B Indicate elevation datum used for the elevations in item Datum used for building elevations must be the same a a) Top of bottom floor (including basement, crawlspace, 	truction of the buildin L–V30, V (with BFE), A ed in Item A7. In Puer ––––––––––––––––––––––––––––––––––––	ng is complete. AR, AR/A, AR/AE, to Rico only, ente tical Datum: <u>NG</u> V. X NGVD 192: FE. <u>9 9</u>	AR/A1-A30, AR/AH, er meters. GVD 1929 Ele 9	Finished Construction AR/AO. Complete Items vation = 10.928 feet			
 *A new Elevation Certificate will be required when const C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V1 C2.a–h below according to the building diagram specific Benchmark Utilized: Sarasota County BM 485 B Indicate elevation datum used for the elevations in item Datum used for building elevations must be the same a a) Top of bottom floor (including basement, crawlspace, b) Top of the next higher floor 	truction of the buildin L–V30, V (with BFE), A ed in Item A7. In Puer Ver us a) through h) below s that used for the B or enclosure floor)	ng is complete. AR, AR/A, AR/AE, to Rico only, ente rtical Datum: <u>NG</u> V. X NGVD 1929 FE. <u>9 . 9</u> <u>n/a .</u>	AR/A1–A30, AR/AH, er meters. BVD 1929 Eler 9 🗌 NAVD 1988 🖸 Check the mea 🖾 feet feet	Finished Construction AR/AO. Complete Items vation = 10.928 feet Other/Source:			
 *A new Elevation Certificate will be required when const C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V2 C2.a–h below according to the building diagram specifie Benchmark Utilized: Sarasota County BM 485 B Indicate elevation datum used for the elevations in item Datum used for building elevations must be the same a a) Top of bottom floor (including basement, crawlspace, b) Top of the next higher floor c) Bottom of the lowest horizontal structural member (W 	truction of the buildin L–V30, V (with BFE), A ed in Item A7. In Puer Ver us a) through h) below s that used for the B or enclosure floor)	ng is complete. AR, AR/A, AR/AE, to Rico only, enter tical Datum: <u>NG</u> w. ⊠ NGVD 1929 FE. <u>9 9</u> <u>9 9</u> <u>n/a</u> .	AR/A1–A30, AR/AH, er meters. SVD 1929 Ele 9 □ NAVD 1988 □ Check the mea ♀ feet ♀ feet	Finished Construction AR/AO. Complete Items vation = 10.928 feet Other/Source: Surement used. meters meters meters meters			
 *A new Elevation Certificate will be required when const C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V1 C2.a–h below according to the building diagram specific Benchmark Utilized: Sarasota County BM 485 B Indicate elevation datum used for the elevations in item Datum used for building elevations must be the same a a) Top of bottom floor (including basement, crawlspace, b) Top of the next higher floor 	truction of the buildin L–V30, V (with BFE), A ed in Item A7. In Puer ver is a) through h) below is that used for the B or enclosure floor) / Zones only) g the building	ng is complete. AR, AR/A, AR/AE, to Rico only, ente rtical Datum: <u>NG</u> V. X NGVD 1929 FE. <u>9 . 9</u> <u>n/a .</u>	AR/A1–A30, AR/AH, er meters. BVD 1929 Eler 9 🗌 NAVD 1988 🖸 Check the mea 🖾 feet feet	Finished Construction AR/AO. Complete Items vation = 10.928 feet Other/Source: surement used. meters meters			
 *A new Elevation Certificate will be required when consist C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V2 C2.a–h below according to the building diagram specifie Benchmark Utilized: Sarasota County BM 485 B Indicate elevation datum used for the elevations in item Datum used for building elevations must be the same a a) Top of bottom floor (including basement, crawlspace, b) Top of the next higher floor c) Bottom of the lowest horizontal structural member (Va) d) Attached garage (top of slab) e) Lowest elevation of machinery or equipment servicing (Describe type of equipment and location in Commer f) Lowest adjacent (finished) grade next to building (LAC) 	truction of the buildin L–V30, V (with BFE), A ed in Item A7. In Puer 	ng is complete. AR, AR/A, AR/AE, to Rico only, enter tical Datum: NG w. ⊠ NGVD 1929 FE. 9 9 n/a . 9 7 9 7 9 7 9 4	AR/A1–A30, AR/AH, er meters. BVD 1929 Ele 9 NAVD 1988 C Check the mea Check the mea Get Get Get Get Get Get Get Check	Finished Construction AR/AO. Complete Items vation = 10.928 feet Other/Source: Other/Source: surement used. meters meters meters meters meters meters meters meters			
 *A new Elevation Certificate will be required when const C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V2 C2.a–h below according to the building diagram specific Benchmark Utilized: Sarasota County BM 485 B Indicate elevation datum used for the elevations in item Datum used for building elevations must be the same a a) Top of bottom floor (including basement, crawlspace, b) Top of the next higher floor c) Bottom of the lowest horizontal structural member (Vd) Attached garage (top of slab) e) Lowest elevation of machinery or equipment servicing (Describe type of equipment and location in Commer 	truction of the buildin L–V30, V (with BFE), A ed in Item A7. In Puer ——————————————————— ver us a) through h) below is that used for the B or enclosure floor) / Zones only) g the building nts) G) VG)	ng is complete. AR, AR/A, AR/AE, to Rico only, enter tical Datum: NG w. ⊠ NGVD 1929 FE. 9 9 n/a . 9 7 9 7 9 7	AR/A1–A30, AR/AH, er meters. SVD 1929 Ele 9 NAVD 1988 C Check the mea Check the mea Check the mea Check the mea feet feet feet feet feet feet feet feet feet feet feet feet feet	Finished Construction AR/AO. Complete Items vation = 10.928 feet Other/Source: Other/Source: surement used. meters			
 *A new Elevation Certificate will be required when consist C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V2 C2.a–h below according to the building diagram specifie Benchmark Utilized: Sarasota County BM 485 B Indicate elevation datum used for the elevations in item Datum used for building elevations must be the same a a) Top of bottom floor (including basement, crawlspace, b) Top of the next higher floor c) Bottom of the lowest horizontal structural member (V d) Attached garage (top of slab) e) Lowest elevation of machinery or equipment servicing (Describe type of equipment and location in Commer f) Lowest adjacent (finished) grade next to building (LAG g) Highest adjacent grade at lowest elevation of deck or structural support 	truction of the buildin L-V30, V (with BFE), A ed in Item A7. In Puer 	ng is complete. AR, AR/A, AR/AE, to Rico only, enter trical Datum: <u>NG</u> (NGVD 1929) FE. <u>9 9</u> <u>n/a</u> <u>9 7</u> <u>9 7</u> <u>9 4</u> <u>9 7</u> <u>9 7</u> <u>9 4</u> <u>9 7</u> <u>9 7</u>	AR/A1-A30, AR/AH, er meters. BVD 1929 Ele 9 NAVD 1988 C Check the mea Check the mea Check the mea feet feet feet feet feet feet feet feet feet feet feet feet feet feet feet	Finished Construction AR/AO. Complete Items vation = 10.928 feet Other/Source: Other/Source: surement used. meters			
 *A new Elevation Certificate will be required when consist C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V2 C2.a–h below according to the building diagram specific Benchmark Utilized: Sarasota County BM 485 B Indicate elevation datum used for the elevations in item Datum used for building elevations must be the same a a) Top of bottom floor (including basement, crawlspace, b) Top of the next higher floor c) Bottom of the lowest horizontal structural member (V d) Attached garage (top of slab) e) Lowest elevation of machinery or equipment servicing (Describe type of equipment and location in Commer f) Lowest adjacent (finished) grade next to building (LAG g) Highest adjacent grade at lowest elevation of deck or structural support 	truction of the buildin L-V30, V (with BFE), A ed in Item A7. In Puer 	ng is complete. AR, AR/A, AR/AE, to Rico only, enter trical Datum: <u>NG</u> (AR, AR/A, AR/AE, to Rico only, enter (AR, AR/A, AR/AE, (AR, AR/AE, (AR, AR/AE, (AR, AR, AR, AR, AR, AR, AR, AR, AR, AR,	AR/A1-A30, AR/AH, er meters. CVD 1929 Elev 9 NAVD 1988 C Check the mea Check the mea Get Get Get Get Get Get Get Get	Finished Construction AR/AO. Complete Items vation = 10.928 feet Other/Source: Other/Source: surement used. meters			
 *A new Elevation Certificate will be required when consists C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V2 C2.a–h below according to the building diagram specifies Benchmark Utilized: Sarasota County BM 485 B Indicate elevation datum used for the elevations in item Datum used for building elevations must be the same a a) Top of bottom floor (including basement, crawlspace, b) Top of the next higher floor c) Bottom of the lowest horizontal structural member (Vd) Attached garage (top of slab) e) Lowest elevation of machinery or equipment servicing (Describe type of equipment and location in Commer f) Lowest adjacent (finished) grade next to building (LAG g) Highest adjacent grade at lowest elevation of deck or structural support 	truction of the buildin L-V30, V (with BFE), A ed in Item A7. In Puer 	ng is complete. AR, AR/A, AR/AE, to Rico only, enter tical Datum: NG M NGVD 1929 FE. 9 9 n/a 	AR/A1-A30, AR/AH, er meters. SVD 1929 Ele 9 NAVD 1988 C Check the mea Check the mea Get Feet Feet Feet Feet Feet Feet Feet Feet Feet Feet Feet Feet Feet Steet Feet	Finished Construction AR/AO. Complete Items vation = 10.928 feet Other/Source: Other/Source: surement used. meters			
 *A new Elevation Certificate will be required when consists C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V2 C2.a–h below according to the building diagram specific Benchmark Utilized: Sarasota County BM 485 B Indicate elevation datum used for the elevations in item Datum used for building elevations must be the same a a) Top of bottom floor (including basement, crawlspace, b) Top of the next higher floor c) Bottom of the lowest horizontal structural member (Vd) Attached garage (top of slab) e) Lowest elevation of machinery or equipment servicing (Describe type of equipment and location in Commer f) Lowest adjacent (finished) grade next to building (LAG g) Highest adjacent grade at lowest elevation of deck or structural support SECTION D – SURVE This certification is to be signed and sealed by a land surveyou formation. <i>I certify that the information on this Certificate repunderstand that any false statement may be punishable by find.</i> Check here if comments are provided on back of form. Certifier's Name	truction of the buildin L-V30, V (with BFE), A ed in Item A7. In Puer ver s a) through h) below s that used for the B or enclosure floor) / Zones only) g the building its) G) KG) stairs, including TYOR, ENGINEER, r, engineer, or architec resents my best effort e or imprisonment univ Were latitude and lo	ng is complete. AR, AR/A, AR/AE, to Rico only, enter tical Datum: NG NGVD 1929 FE. 9 9 n/a 	AR/A1–A30, AR/AH, er meters. SVD 1929 Eler 9	Finished Construction AR/AO. Complete Items vation = 10.928 feet Other/Source: Surement used. meters PLACE			
 *A new Elevation Certificate will be required when consist C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V2 C2.a–h below according to the building diagram specific Benchmark Utilized: Sarasota County BM 485 B Indicate elevation datum used for the elevations in item Datum used for building elevations must be the same a a) Top of bottom floor (including basement, crawlspace, b) Top of the next higher floor c) Bottom of the lowest horizontal structural member (Vd) Attached garage (top of slab) e) Lowest elevation of machinery or equipment servicing (Describe type of equipment and location in Commer f) Lowest adjacent (finished) grade next to building (LAG g) Highest adjacent grade at lowest elevation of deck or structural support ECTION D – SURVE This certification is to be signed and sealed by a land surveyou information. <i>I certify that the information on this Certificate reprindent servicing that any false statement may be punishable by find that any false statement may be punishable by find the information on this Certificate reprindent servicing that any false statement may be punishable by find that any false statement may be punishable by find the information on this Certification servicing that the information on this Certificate reprindent servicing that the information on this Certificate reprindent servicing that the information on this Certificate reprindent servicing that any false statement may be punishable by find the information on this Certificate reprindent servicing that the information on this Certificate reprindent servicing that the information on this Certificate reprindent servicing that the information on this Certifi</i>	truction of the buildin L-V30, V (with BFE), A ed in Item A7. In Puer ver s a) through h) below s that used for the B or enclosure floor) / Zones only) g the building its) G) KG) stairs, including TYOR, ENGINEER, r, engineer, or architec resents my best effort e or imprisonment univ Were latitude and lo	ag is complete. AR, AR/A, AR/AE, to Rico only, enter trical Datum: NG M NGVD 1929 FE. 9 9 n/a 9 7 9 7 9 7 9 7 9 7 9 7 9 7 9 7	AR/A1–A30, AR/AH, er meters. SVD 1929 Eler 9	Finished Construction AR/AO. Complete Items vation = 10.928 feet Other/Source: surement used. meters			
 *A new Elevation Certificate will be required when consists C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V2 C2.a-h below according to the building diagram specific Benchmark Utilized: Sarasota County BM 485 B Indicate elevation datum used for the elevations in item Datum used for building elevations must be the same a a) Top of bottom floor (including basement, crawlspace, b) Top of the next higher floor c) Bottom of the lowest horizontal structural member (Vd) Attached garage (top of slab) e) Lowest elevation of machinery or equipment servicing (Describe type of equipment and location in Commer f) Lowest adjacent (finished) grade next to building (LAG g) Highest adjacent grade at lowest elevation of deck or structural support SECTION D – SURVE This certification is to be signed and sealed by a land surveyou formation. <i>I certify that the information on this Certificate repulated that any false statement may be punishable by find.</i> Check here if comments are provided on back of form. Certifier's Name Larry J Sharp Title	truction of the buildin L-V30, V (with BFE), A ed in Item A7. In Puer 	ag is complete. AR, AR/A, AR/AE, to Rico only, enter trical Datum: NG M NGVD 1929 FE. 9 9 n/a 9 7 9 7 9 7 9 7 9 7 9 7 9 7 9 7	AR/A1–A30, AR/AH, er meters. SVD 1929 Eler 9	Finished Construction AR/AO. Complete Items vation = 10.928 feet Other/Source: Surement used. meters PLACE			

FEMA Form 086-0-33 (Revised 7/12)

See reverse side for continuation.

Replaces all previous editions.

ELEVATION CERTIFICATE, page 2

,

IMPORTANT: In these spaces, copy the co		FOR INSURANCE COMPANY USE						
Building Street Address (including Apt., Uni 910 Neptune Drive	t, Suite, and/or Bldg. No.) or PO. Ro			Policy Number:				
City	State	ZIP Code		Company NAIC Nu	mber:			
Englewood	FL	34223		1				
SECTION D - SURVEYOR, ENGINEER, OR ARCHITECT CERTIFICATION (CONTINUED)								
Copy both sides of this Elevation Certificate for (1) community official, (2) insurance agent/company, and (3) building owner.								
Comments C2.e) Air Conditioner on co This addition has one Smai Magellan Triton 1500 GPS	ncrete slab located outside of the t Vent Installed and 13 other no	ne building. on-engineered	openings.					
Signature The De	ins	Date /-	28-14					
SECTION E - BUILDING ELEVAT				O AND ZONE A	(WITHOUT BFE)			
For Zones AO and A (without BFE), complete For Items E1–E4, use natural grade, if availa	e Items E1-E5. If the Certificate is in	ntended to suppo	rt a LOMA or LOME					
E1. Provide elevation information for the foll grade (HAG) and the lowest adjacent grade	lowing and check the appropriate bo ade (LAG).	oxes to show whe	ther the elevation i	s above or below th	ne highest adjacent			
a) Top of bottom floor (including baseme		• • • • • • • • • • • • • • • • • • • •	🗌 feet 🔲 me		below the HAG.			
b) Top of bottom floor (including baseme			🗌 feet 🛛 me		\Box below the LAG.			
E2. For Building Diagrams 6-9 with perman								
the next higher floor (elevation C2.b in t E3. Attached garage (top of slab) is	ne diagrams) of the building is _	· · · · · · · · · · · · · · · · · · ·						
					below the HAG.			
E4. Top of platform of machinery and/or equ					below the HAG.			
E5. Zone AO only: If no flood depth number ordinance? Yes No Unkno	wn. The local official must certify th	is information in	Section G.	ne community's floo	odplain management			
SECTION F -	PROPERTY OWNER (OR OWN	ER'S REPRES	ENTATIVE) CER	TIFICATION				
The property owner or owner's authorized re Zone AO must sign here. The statements in	presentative who completes Section	ns A. B. and F for	Zone A (without a		mmunity-issued BFE) or			
Property Owner or Owner's Authorized Repre	esentative's Name							
Address		City	S	ate ZIP C	ode			
Signature		Date	Te	elephone				
Comments								
					< here if attachments.			
	SECTION G - COMMUNITY	NFORMATION	(OPTIONAL)					
The local official who is authorized by law or o	ordinance to administer the communi	tv's floodolain ma	agement ordinance	e can complete Sec	tions A, B, C (or E), and			
G of this Elevation Certificate. Complete the a								
G1. The information in Section C was t who is authorized by law to certify	elevation information. (Indicate the	source and date	of the elevation d	licensed surveyor, ata in the Commer	engineer, or architect			
G2. A community official completed Sec	tion E for a building located in Zone	A (without a FEN	A-issued or comm	unity-issued BFE) o	r Zone AO.			
G3. 🔲 The following information (Items G	4–G10) is provided for community f	loodplain manag	ement purposes.					
G4. Permit Number	G5. Date Permit Issued	G6.	Date Certificate Of	Compliance/Occu	pancy Issued			
		al Improvement						
G8. Elevation of as-built lowest floor (includ	_							
G9. BFE or (in Zone AO) depth of flooding a G10. Community's design flood elevation:	t the building site:	·						
		Tial -	feet mete	ers Datum				
Community Name		Title			· · · · · · · · · · · · · · · · · · ·			
-		Telephone						
Signature		Date						
Comments								

Check here if attachments.

Building Photographs

See Instructions for Item A6.

Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Box No. 1910 Neptune Drive

For Insurance Company Use: Policy Number

Company NAIC Number

City Englewood State FL ZIP Code 34223

If using the Elevation Certificate to obtain NFIP flood insurance, affix at least two building photographs below according to the instructions for Item A6. Identify all photographs with: date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View." If submitting more photographs than will fit on this page, use the Continuation Page, following.

Front view 1-27-2014



Rear View 1-27-2014







ICC-ES Evaluation Report

Most Widely Accepted and Trusted

FSR-2074 Reissued February 1, 2009 This report is subject to re-examination in two years.

A Subsidiary of the International Code Council®

unlatch, allowing the plate to rotate out of the way and allow flow. The water level stabilizes, equalizing the lateral forces. Each unit is fabricated from stainless steel, and each opening provides 76 square inches (49 032 mm²) of net free area for flood mitigation in the open position. The SmartVENT™ Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-521 units each contain two vertically arranged openings per unit, providing 152 square inches (98 064 mm²) of net free area for flood mitigation in the open position.

wanaad wada aya uu wanafauu

3.2 Engineered Opening:

The AFFVs comply with the design principle noted in Section 2.6.2.2 of ASCE/SEI 24 for a maximum rate of rise and fall of 5.0 feet per hour (0.423 mm/s). In order to comply with the engineered opening requirement of ASCE/SEI 24, Smart Vent AFFVs must be installed in accordance with Section 4.0.

3.3 Model Sizes:

The FloodVENTTM Model #1540-520, Smart/VENTTM Model #1540-510, FloodVENTTM Model #1540-520 524, and Smart/VENTTM Overhead Door Model #1540-514 units measure 15¹/₄ inches wide by 7³/₄ inches high (400 by 196.9 mm). The Wood Wall Flood Model #1540-574 and Wood Wall Flood Overhead Door Model #1540-574 and Wood Wall Flood Overhead Door Model #1540-574 units measure 14 inches wide by 8³/₄ inches high (355.6 by 222.25 mm). The Smart/VENTTM Stacking Model #1540-574 measure 16 inches wide by 16 inches high (466.4 by 406.4 mm).

:noitslitnev 4.5

The SmartVEVT® Model #1540-510 and SmartVEVT® Verhead Door Model #1540-514 both have screen covers overhead Door Model #1540-514 both have screen covers, with ¹/4-inch-by-¹/4-inch (6.35 by 6.35 mm²) of net free area to yielding 51 square inches (32 903 mm²) of net free area to supply natural ventilation. The SmartVEVT^{*M} Stacking model #1540-511 consists of two Model #1540-516 units in one assembly, and provides 102 square inches (65 806 one assembly, and provides 102 square inches (65 806 mm²) of net free area to supply natural ventilation. Other and the start of the matural ventilation. The start of the matural ventilation of the area to supply natural ventilation. Other one assembly, and provides 102 square inches (65 806 mm²) of net free area to supply natural ventilation. Other one assembly, and provides 102 square inches (65 806 mm²) of net free area to supply natural ventilation. Other one assembly, and provides 102 square inches (65 806 mm²) of net free area to supply natural ventilation. Other one assembly, and provides 102 square inches (65 806 mm²) of net free area to supply natural ventilation. Other one assembly, and provides 102 square inches (65 806 mm²) of net free area to supply natural ventilation. Other one assembly, and provides 102 square inches (65 806 mm²) of net free area to supply natural ventilation. Other one assembly, and provides 102 square inches (65 806 mm²) of net free area to supply natural ventilation. Other one assembly a

NOITALLATZNI 0.4

Smart/VENT[®] and Flood/VENTTM are designed to be installed into walls or overhead doors of existing or new construction from the exterior side. Installation of the vents must be in accordance with the manufacturer's instructions, the applicable code and this report. The mounting straps allow mounting in wood, masonry and

concrete walls up to 12 inches (305 mm) thick. In order to



Section: 10230-Aents Section: 10-SPECIALTIES

REPORT HOLDER:

SMART VENT®, INC. 460 AUDBRO DRIVE, SUITE 2B PITMAN, NEW JERSEY 08071 (856) 307-1468 (856) 307-1468 <u>evai@smartvent.com</u>

EVALUATION SUBJECT:

SMART VENT® AUTOMATIC FOUNDATION FLOOD VENTS: FLOODVENT™ MODEL #1640-630; JELOODVENT™ STACKING MODEL #1640-630; JELOODVENT™ MODEL #1640-610; SMARTVENT™ STACKING MODEL #1640-634; PLOOD OVERHEAD DOOR MODEL #1640-634; FLOOD OVERHEAD DOOR MODEL #1640-634; SMARTVENT™ OVERHEAD T

1.0 EVALUATION SCOPE

Compliance with the following codes:

- (Cal) "eboC pribling lenoitemetril 8002 =
- 2006 International Residential Code[®] (IRC)
- Properties evaluated:
- Physical operation
- woft 1936VV m

2.0 USES

The Smart Vent[®] units are automatic foundation flood vents (AFFVs) employed to equalize hydrostatic pressure on nonfire-resistance-rated foundation walls, rolling-type overhead doors and building walls subject to rising or falling flood waters. Certain models also allow natural ventilation in accordance with Section 1203 of the IBC or ventilation in accordance with Section 1203 of the IBC or ventilation in accordance with Section 1203 of the IBC or ventilation in accordance with Section 1203 of the IBC or ventilation and the IRC.

3.0 DESCRIPTION

3.1 General:

When subjected to pressure from rising water, the Smart Vent[®] AFFVs disengage, then pivot open to allow flow in either direction to equalize water level and hydrostatic pressure from one side of the foundation to the other. The AFFV pivoting door is normally held in the closed position water, the buoyant release device. When subjected to rising water, the buoyant release device causes the unit to



Page 1 of 2

ISNV)

COPYNGHI @ 2009

comply with the engineered opening design principle noted in Section 2.6.2.2 of ASCE/SEI 24, the Smart Vent[®] AFFVs must be installed as follows:

- With a minimum of two openings on different sides of each enclosed area
- With a minimum of one AFFV for every 200 square feet (18.6 m²) of enclosed area, except that the SmartVENT[™] Stacking Model #1540-511 and FloodVENT[™] Stacking Model #1540-521 must be installed with a minimum of one AFFV for every 400 square feet (37.2 m²) of enclosed area.
- Below the base flood elevation
- With the bottom of the AFFV located a maximum of 12 inches (305.4 mm) above grade.

5.0 CONDITIONS OF USE

The Smart Vent[®] AFFVs described in this report comply with, or are suitable alternatives to what is specified in, those codes listed in Section 1.0 of this report, subject to the following conditions:

- 5.1 The Smart Vent[®] AFFVs must be installed in accordance with this report, the applicable code and the manufacturer's installation instructions. In the event of a conflict, the instructions in this report govern.
- 5.2 The Smart Vent[®] AFFVs must not be used in the place of "breakaway walls" in coastal high hazard areas, but are permitted for use in conjunction with breakaway walls in other areas.

6.0 EVIDENCE SUBMITTED

Data in accordance with the ICC-ES Acceptance Criteria for Automatic Foundation Flood Vents (AC364), dated October 2007.

7.0 IDENTIFICATION

The Smart VENT[®], models recognized in this report must be identified by a label bearing the manufacturer's name (Smart Vent, Inc.), the model number, and the evaluation report number (ESR-2074).