FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

This form is to be used for: 1) New/Emergency Program construction in Special Flood Hazard Areas, 2) Pre-FIRM construction after September 30, 1982; 3) Post-FIRM construction; and, 4) Other buildings rated as Post-FIRM rules.

ADDRESS

OMB 3067-0077 Expires: June 1984

BUILDING OWNER'S

NAME

Homemasters Construction
PROPERTY LOCATION (Lot and Block numbers and address if available)

Lots 18345&18346, South Venice Unit 69-Orchis Road Venice, Florida

CTION I ELIGIBILITY CERTIFICATION (	rchitect, or Surve	eyor)		Control of the second
MMUNITY NO. PANEL NO. SUFFIX DATE OF FI	IRM FIRM ZONE	DATE OF CONSTR.	BASE FLOOD ELEV (In AO Zone, use depth)	BUILDING IS  [] New/Emergency [] Pre-FIRM Reg [] Post-FIRM Reg
It is intended that the building described ordinance. The certifier may rely or of ft, NGVD. Failure to the community's flood plain manage.	n community reco	ords. The lowest fluilding at this eleva	oor (including basem	community's flood plain ent) will be at an elevation uilding in violation of
S NO The building described above has to ordinance based on elevation data If NO is checked, attach copy of variance based on the copy of variance based on	and visual inspec	ction or other reas	h the community's flo onable means.	tood plain management
ES NO The mobile home located at the ad	dress described a	above has been tie	d down (anchored) in	n compliance with the tions.
MOBILE HOME MAKE MODEL	27 m	OF MANUFACTU		
Community Permit Official or Registered Pro	fessional Enginee	er, Architect, or Su	rveyor)	
AME		ADDRESS		
ITLE CI	ITY		STATE	ZIP
IGNATURE	oct merchan in	DATE	PHONE	
ECTION II ELEVATION CERTIFICATION	(Certified by a Lo Architect, or Sur	ocal Community Perveyor.)	ermit Official or a Heg	pistered Professional Enginee
at an elevation of +11 an elevation of +11	3 42 feet, NGVE	).	ribed above has the hi	ottom of the lowest floor bean
at an elevation of + 1 an elevation of + 1 IRM ZONES V, V1-V30: I certify that the beat an elevation of is at an elevation of is at an elevation of feet, NGVD. The certify that the building at eet, NGVD. The elevation of the highest adjacet, NGVD. The elevation of the highest adjacet is certify to the best of my knowledge, inform	uilding at the property local cent grade next to CATION (Certificant and belief)	perty location desc, NGVD (mean sea lev).  perty location desc, NGVD (mean sea let), NGVD.  I that the building a highest adjacent gotton described about the building is ation by a Register for the building.	ribed above has the bear level), and the average of the property location rade next to the building over has the lowest flower has the lowest flowest. No	ottom of the lowest floor bean age grade at the building site of the building is watertight, with ability of resisting hydrostat
IRM ZONES V, V1-V30: I certify that the biat an elevation of is at an elevation of is at an elevation of is at an elevation of feet, NGVD. The feet, NGVD. The elevation of the highest adjacet, NGVD. The elevation of the highest adjacet, NGVD. The elevation of the highest adjacet is under the property of the passion of t	and the property local cent grade next to the property local cent grad	perty location desc., NGVD (mean sea lev o).  It that the building a highest adjacent go the building is ation by a Register for the thickness of the building structural compose caused by the sea of floodproofing will enter the building the flood to prevent the credited for the	ribed above has the bear level), and the average of the property location rade next to the building over has the lowest flower feet, NC ed Professional Enginesis designed so that the next having the cap flood depths, pressure be achieved with hurding when floods up the next of water (e.g.	ottom of the lowest floor beam age grade at the building site of described above has the loweng is
at an elevation of +11 at an elevation of is at an elevation of is at an elevation of elevation of teet, NGVD. The elevation of the highest adja and hydrodynamic loads and effects of buoyorces associated with the base flood.  YES NO In the event of flooding (Human intervention cur unless measures doors and windows).  YES NO Will the building be of the answer to both questions is YES, the floompleted and certified instead. Complete but at an elevation of is at an elevation of is at an elevation of elevation of the highest adja and provided in the passion of the passion of the passion of the second of the second of the event of flooding (Human intervention cur unless measures doors and windows).  YES NO Will the building be of the answer to both questions is YES, the floompleted and certified instead. Complete but the second of th	det, NG leet, NG leet	perty location desc, NGVD (mean sea lev).  perty location desc, NGVD (mean sea lev).  I that the building a highest adjacent g ation described about the building is ation by a Register f, that the building structural composible caused by the leve of floodproofing will enter the building the flood to prevent the flood to prevent the credited for and floodproofing	ribed above has the bear level), and the average of the property location rade next to the building over has the lowest flower feet, NC ed Professional Enginesis designed so that the next having the cap flood depths, pressure be achieved with hurding when floods up the next of water (e.g.	ottom of the lowest floor bean age grade at the building site of the building site of the building site of the building site of the building is watertight, with ability of resisting hydrostates velocities, impact and uplication intervention? The building metal shields over the actual lowest floor must the site of the base flood level october the actual lowest floor must the site of the building metal shields over the actual lowest floor must the site of the base flood level october over the actual lowest floor must the site of the base flood level october over the actual lowest floor must the site of the base flood level october over the actual lowest floor must the site of the base flood level october over the actual lowest floor must the site of the
at an elevation of +11 an elevation of +11 an elevation of +11 an elevation of +11 IRM ZONES V, V1-V30: I certify that the bit at an elevation of is at an elevation of the bighest adjacet, NGVD. The elevation of the highest adjacet, NGVD. The elevation of the highest adjacet, NGVD. The elevation of the highest adjacet NGVD. The elevation of the highest adjacet NGVD. The elevation of the highest adjacet NGVD. The elevation of the passe and hydrodynamic loads and effects of buoy orces associated with the base flood.  YES NO In the event of floodin (Human intervention cur unless measures doors and windows).  YES NO Will the building be completed and certified instead. Complete befirm ZONES A, A1,-A30, V1-V30, AO and AFFIRM ZONES A, A1,-A30, V1-V30, AO and AFFIRM ZONES A, A1,-A30, V1-V30, AO and AFFIRM ZONES A.	3. 42 feet, NG 2. 00 feet, NGVD  uilding at the proy feet  of	perty location desc, NGVD (mean sea lev).  perty location desc, NGVD (mean sea lev).  I that the building a highest adjacent g ation described about the building is ation by a Register f, that the building structural composible caused by the leve of floodproofing will enter the building the flood to prevent the flood to prevent the credited for and floodproofing	ribed above has the bear level), and the average of the property location rade next to the building over has the lowest flour feet, NC led Professional Enginest having the cap flood depths, pressure be achieved with hur ding when floods up that entry of water (e.g. rating purposes and certificates.	ottom of the lowest floor beam age grade at the building site of the building site of the building site of the building site of the building is watertight, with ability of resisting hydrostatives velocities, impact and uplication in the building metal shields over the actual lowest floor must be site of the base flood level october of the actual lowest floor must be site of the base floor must b
at an elevation of +11 at an elevation of is at an elevation of is at an elevation of elevation of feet, NGVD. The or elevation of feet, NGVD. The law at a feet, NGVD. The elevation of the highest adjance of the highest adjance of the highest adjance of the law at a feet, NGVD. The elevation of the highest adjance of the law at a feet, NGVD. The elevation of the highest adjance of the passion of the law at a feet, NGVD. The elevation of the highest adjance of the passion of the law at a feet, NGVD. The elevation of the highest adjance of the passion of the law at a feet, NGVD. The elevation of the highest adjance of the passion of the law at a feet, NGVD. The elevation of the highest adjance of the passion of the law at a feet, NGVD. The elevation of the highest adjance of the passion of the law at a feet, NGVD. The elevation of the highest adjance of the passion of the law at a feet, NGVD. The elevation of the highest adjance of the passion of the	3. 42 feet, NG 2. 00 feet, NGVD  uilding at the proy feet  ROGRAM: I certify the elevation of the the property location action, and belief age of water and vancy that would  ng, will this degree means that water are taken prior to accupied as a resi coodproofing can oth the elevation  d:  II □ BOTH SI  COMPAR	perty location desc.  NGVD (mean sea lev.)  Ithat the building a highest adjacent guition described about the building is ation by a Register structural composite caused by the sea of floodproofing will enter the building the flood to prevent the flood proofing the credited for and floodproofing Certified ECTIONS II AND INT NAME	ribed above has the bia level), and the average of a level), and the average of the property location rade next to the building over has the lowest florated professional Enginest having the capflood depths, pressure be achieved with hurding when floods up the entry of water (e.g. rating purposes and certificates.	ottom of the lowest floor bean age grade at the building sit of described above has the loweng is feet, NGV feet, NGV feet or Architect)  the building is watertight, with ability of resisting hydrostates velocities, impact and upleman intervention? To the base flood level octobelling metal shields over the actual lowest floor must be ion is feet, (NGVI)  LICENSE NO. (or Affix Seal
at an elevation of +11 at an elevation of is at an elevation of is at an elevation of elevation of feet, NGVD. The or elevation of the highest adja and the feet of the highest adja bet, NGVD. The elevation of the highest adja bet, NGVD.	3. 42 feet, NG 2. 00 feet, NGVD  uilding at the proy feet  ROGRAM: I certify the elevation of the the property location action, and belief age of water and vancy that would  ng, will this degree means that water are taken prior to accupied as a resi coodproofing can oth the elevation  d:  II □ BOTH SI  COMPAR	perty location desc. NGVD (mean sea lev) Note: NGVD (mean sea lev) Note: NGVD. NGVD. Note: NGVD.	ribed above has the bia level), and the average of a level), and the average of the property location rade next to the building over has the lowest florated professional Enginest having the capflood depths, pressure be achieved with hurding when floods up the entry of water (e.g. rating purposes and certificates.	ottom of the lowest floor bean age grade at the building site of described above has the loweng is feet, NGV for elevation of says.  The building is watertight, with ability of resisting hydrostatives velocities, impact and upliman intervention? The base flood level octubed the actual lowest floor must be says. LICENSE NO. (or Affix Seal 2670
at an elevation of +11 an elevation of +11 an elevation of +11 an elevation of +11 an elevation of the property of the proof elevation of the proof elevation of the highest adjacet, NGVD. The elevation of the highest adjacet of the proof the proof of the highest adjacet of the proof the proof of	and the property local cent grade next to the property local cent grad	perty location desc, NGVD (mean sea lev).  That the building a highest adjacent g ation described about the building is ation by a Register ation by a Register ation by a Register at the building structural composite caused by the sea of floodproofing will enter the building the flood to prevent the flood to prevent the credited for and floodproofing Certified ECTIONS II AND INTERNAL SULVE THAT THE STANKE THAT THE SULVE TH	ribed above has the bear level), and the average of a level), and the average of a level), and the average of the property location rade next to the building over has the lowest flowed Professional Enginests having the capflood depths, pressure be achieved with hurding when floods up the entry of water (e.g. rating purposes and certificates.  I Floodproofed Elevation (Check One)	ottom of the lowest floor beam age grade at the building site of described above has the loweng is feet, NGVI feet, NGVI feet or Architect)  the building is watertight, with ability of resisting hydrostatics velocities, impact and upliman intervention? to the base flood level octubely building metal shields over the actual lowest floor must be ion is feet, (NGVI license NO. (or Affix Seal)
at an elevation of +11 at an elevation of +11 at an elevation of is at an elevation of is at an elevation of elevation of feet, NGVD. The or elevation of the highest adja  SECTION III FLOODPROOFING CERTIFIC certify to the best of my knowledge, informable substantially impermeable to the passified hydrodynamic loads and effects of buoy forces associated with the base flood.  YES NO Higher Holding be concerned by the passified hydrodynamic loads and effects of buoy forces associated with the base flood.  YES NO Higher Holding be concerned by the passified hydrodynamic loads and effects of buoy forces and windows).  YES NO Higher Holding be concerned by the passified instead. Complete by the passified instead. Complete by the passified instead. Complete by the passified instead. The passified instead and certified instead. The passified instead and passified instead and passified instead. The passified instead and passified instead. The passified instead and passif	and AZ feet, NGC 100 feet of 100 f	perty location desc.  NGVD (mean sea lev)  Ithat the building a highest adjacent go the building is ation by a Register structural composite caused by the sea of floodproofing will enter the building the flood to prevent the flood to prevent the caused by the sea of floodproofing certified the caused by the sea of floodproofing the caused by the sea of floodproofing the flood to prevent the flood to prevent the caused by the sea of floodproofing certified the caused by the sea of floodproofing the caused floodproofing certified the caused by the sea of floodproofing certified the caused by	ribed above has the bear level), and the average of a level), and the average of a level), and the average of the property location rade next to the building over has the lowest flowed Professional Enginests having the capflood depths, pressure be achieved with hurding when floods up the entry of water (e.g. rating purposes and certificates.  I Floodproofed Elevation (Check One)	ottom of the lowest floor beam age grade at the building site of the building site of the building site of the building site of the building is watertight, with ability of resisting hydrostatives velocities, impact and uplication in the building metal shields over the actual lowest floor must be building