

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

OMB 3067-0077 Expires: July 1984

593-117

ELEVATION CERTIFICATE

This form is to be used for: 1) New/Emergency Program construction in Special Flood Hazard Areas; 2) Pre-FIRM construction after September 30, 1982; 3) Post-FIRM construction; and, 4) Other buildings rated as Post-FIRM rules.

BUILDING OWNER'S

EEMA Lorm 91.21 APR 92

ADDRESS

NAME Pro Contracting

440 Pelican Rd., Venice, Florida 33595

PROPERTY LOCATION (Lot and Block numbers and address if available)

Lots 4417 & 4418, Unit 17, South Venice Subdivision

440 Pelican Road

			Arch	tect, or Survi	eyor)	official or a Re	gistered Professional Enginee
125144	0341	D	5/1/84	FIRM ZONE	DATE OF CONSTR	BASE FLOOD ELEV (In AO Zone use depti	BUILDING IS New/Emergency Pre-FIRM Reg Post-FIRM Reg
of_	nance. The	ft, NGVD	may rely on co	nstruct the bu	be constructed in ords. The lowest fluilding at this elevi	compliance with th	e community's flood plain ment) will be at an elevation building in violation of
YES NO The	building de	escribed and on elev	above has beer ation data and	constructed visual inspec		h the community's onable means.	flood plain management
YES NO The	mobile hor munity's flo	ne locate ood plain	d at the address management of	ss described a ordinance, or	bove has been tie	d down (anchored) h the NFIP Specific	in compliance with the ations:
MOBILE H	OME MAKE		MODEL	YR.	OF MANUFACTUR	RE SERIAL	NO. DIMENSIONS
(Community Pe	ermit Officia	al or Regis	stered Professi	10-sept of the Total Control	r, Architect, or Sui	rveyor)	
TITLE			CITY			STATE	ZIP
SIGNATURE					DATE	PHONE	
SECTION II E	LEVATION	CERTIF	ICATION (Cer	rtified by a Lo			gistered Professional Enginee
IRM ZONES V	/, V1-V30:	at an ele	evation of	feet,	erty location descri NGVD (mean sea		
-	A, A99, AO,	is at an ele	elevation of	g at the property feet, fee	erty location descri NGVD (mean sea t, NGVD.	level), and the aver	rage grade at the building sit
FIRM ZONES A	A, A99, AO, has to t	AH, and the lower	evation of elevation of EMERGENCY st floor elevating is	g at the proping feet, feet PROGRAM: on of feet, NGV	erty location descri NGVD (mean sea t, NGVD. I certify that the I feet, NGVD.	level), and the aver	pottom of the lowest floor bear rage grade at the building sit perty location described abovi le highest adjacent grade nex
SECTION III I certify to the walls substantia and hydrodynar forces associate	A. A99, AO, has to ti FLOODPRC best of my ally impermic loads a ed with the	AH, and the lower he building OFING (Control of the building o	EMERGENCY st floor elevation ge, information the passage of s of buoyancy d.	g at the prop- feet, fee PROGRAM: on of feet, NGV ON (Certificat n, and belief, f water and s that would be	erty location descri NGVD (mean sea t, NGVD. I certify that the I feet, NGVD.	ouilding at the prop The elevation of the d Professional Engi s designed so that ents having the cap bood depths, pressur	perty location described above the highest adjacent grade new the highest adjacent grade new the building is watertight, with ability of resisting hydrostaties velocities, impact and uplications.
SECTION III I certify to the walls substantia and hydrodynar forces associate	FLOODPRC best of my ally imperm mic loads a ad with the O In t (Ht	AH, and the lower he building to the lower he base floor the event uman inte	EMERGENCY EMERGE	g at the propulation feet, fee	erty location descri NGVD (mean seat, NGVD. I certify that the language of the local seat of the loca	puilding at the prop The elevation of the d Professional Engi s designed so that ents having the cap bod depths, pressur- e achieved with human when floods up	perty location described above the highest adjacent grade next energy of the perty location described above the highest adjacent grade next energy of the building is watertight, with ability of resisting hydrostatives velocities, impact and upli
SECTION III II I certify to the walls substantia and hydrodynar forces associate YES \(\text{NS} \) No No If the answer to	best of my ally impermic loads a ed with the cur	at an elecis at an	EMERGENCY st floor elevation ge, information the passage of s of buoyancy d. of flooding, wi rvention means leasures are ta indows). ding be occupi	g at the proposed feet, feet feet, no of feet, NGVI DN (Certificat that would be state water and s that would be state water water prior to the das a reside oofing canno	erty location descri NGVD (mean sea t, NGVD. I certify that the larget, N	puilding at the proposed and the average of the elevation of the development of the elevation of the elevati	perty location described above the highest adjacent grade new meer or Architect) the building is watertight, with the building is watertight, with the servelocities, impact and uplification intervention? to the base flood level octor, bolting metal shields over
SECTION III II Certify to the walls substantia and hydrodynar forces associate YES \(\text{NS} \) NO	FLOODPRC best of my ally impermic loads a ed with the Cur door D G Will both quest certified ins	AH, and the lower he building to he	EMERGENCY styles for elevation of EMERGENCY styles for elevation ge, information the passage of s of buoyancy d. of flooding, wi rvention means leasures are ta indows). ding be occupi es, the floodbr mplete both the	g at the proposed feet, feet feet, no of feet, NGVI DN (Certificat that would be state water and s that would be state water water prior to the das a reside oofing canno	erty location descri NGVD (mean sea t, NGVD. I certify that the language of the certify that the language of the caused by the first of floodproofing brill enter the building flood to preven the certification of the ce	puilding at the proposed and the average of the elevation of the development of the elevation of the elevati	perty location described above the highest adjacent grade next the building is watertight, with ability of resisting hydrostatives velocities, impact and uplisman intervention? To the base flood level octubeling metal shields over the actual lowest floor must be served.
SECTION III I I certify to the walls substantia and hydrodynar forces associate YES YES NO YES NO YES If the answer to completed and THIS CERTIFIC	best of my ally impermic loads a ed with the cur door	at an elecis at an	EMERGENCY st floor elevation of elevation of elevation of elevation of st floor elevating is CERTIFICATION of the passage of so of buoyancy d. of flooding, wirrention meanineasures are taindows). ding be occupited, the floodbromplete both the D and AH:	g at the prop- feet, feet PROGRAM: on of feet, NGV ON (Certificat n, and belief, f water and s that would be If this degree s that water w ken prior to ti ed as a reside oofing canno e elevation an	erty location descring to the control of the caused by the flood proofing being the control of the caused by the flood to preven the caused flood to preven the caused by the flood to preven the caused by the flood to preven the caused by the caused by the flood to preven the caused by the	puilding at the proposed and the average of the elevation of the discount of the discount of the elevation o	perty location described above the highest adjacent grade next the building is watertight, with ability of resisting hydrostatives velocities, impact and upliman intervention? To the base flood level octobel building metal shields over the actual lowest floor must be on is
SECTION III II I certify to the walls substantia and hydrodynar forces associate YES \(\text{NS} \) No the management of the substantial of the s	best of my ally imperm mic loads a ed with the cur door	at an elecis at an	EMERGENCY st floor elevation ge, information the passage of s of buoyancy d, of flooding, wi rvention means leasures are ta indows). ding be occupi es, the floodbr mplete both the D and AH:	g at the propulation feet, feet feet, no of feet, NGVI DN (Certificat hat would be state water and state would be state water water water prior to the das a reside of ing cannot be elevation and both section feet as a reside of ing cannot be elevation and both section feet as a reside of ing cannot be elevation and both section feet as a reside of ing cannot be elevation and both section feet as a reside of ing cannot be elevation and both section feet as a reside of ing cannot be elevation and both section feet as a reside of ing cannot be elevation and both section feet as a reside of ing cannot be elevation and both section feet as a reside of ing cannot be elevated by the section feet as a residual by the section feet as a residual by the section feet as	erty location descri NGVD (mean seat, NGVD). I certify that the Infect, NGVD. I certify that the Infect, N	puilding at the proposed and the average of the elevation of the development of the elevation of the elevati	perty location described aboving highest adjacent grade next the building is watertight, with ability of resisting hydrostatives velocities, impact and upliman intervention? To the base flood level octubeling metal shields over the actual lowest floor must be on is
SECTION III I I certify to the walls substantia and hydrodynar forces associate YES NOT	best of my ally impermic loads a ed with the cur doo D In 1 (Hu cur doo D In 1) both quest certified ins. A1-A30, V CATION IS AME	at an elecis at an	EMERGENCY st floor elevation ge, information the passage of s of buoyancy d, of flooding, wi rvention means leasures are ta indows). ding be occupi SS, the floodbr mplete both the D and AH:	g at the propulation of the prop	erty location descring VD (mean seat, NGVD) (mean seat, NGVD). I certify that the largest NGVD. I certify	puilding at the proposed and the average of the elevation of the development of the elevation of the development of the elevation of the eleva	perty location described above the highest adjacent grade next the building is watertight, with ability of resisting hydrostatives velocities, impact and upliman intervention? To the base flood level octobelling metal shields over the actual lowest floor must be on is
SECTION III I I certify to the walls substantia and hydrodynar forces associate YES NOT	best of my ally impermic loads a ed with the cur doo D In 1 (Hu cur doo D In 1) both quest certified ins. A1-A30, V CATION IS AME	at an elecis at an	EMERGENCY EMERGENCY EMERGENCY EST floor elevation of ge, information the passage of s of buoyancy d. of flooding, wi rvention means leasures are ta indows). ding be occupi eS, the floodbr mplete both the of and AH: ECTION II	g at the property of the prope	erty location description of the tructural compone caused by the floor to prevent the tructural compone caused by the floor floodproofing being the floor to prevent the floor floor for the floor	puilding at the proposed and the development of the	perty location described above the highest adjacent grade next the building is watertight, with ability of resisting hydrostatives velocities, impact and upliman intervention? To the base flood level octobelling metal shields over the actual lowest floor must be consisted in the actual lowest floor must be consisted in the actual lowest floor floor must be consisted in the actual lowest floor floor must be consisted in the actual lowest floor floor must be consisted in the actual lowest floor floor must be consisted in the actual lowest floor flo
SECTION III I I certify to the walls substantia and hydrodynar forces associate YES NOT	best of my ally impermic loads a ed with the cur doo D In 1 (Hu cur doo D In 1) both quest certified ins. A1-A30, V CATION IS AME	at an elecis at an	EMERGENCY st floor elevation ge, information the passage of s of buoyancy d, of flooding, wi rvention means leasures are ta indows). ding be occupi SS, the floodbr mplete both the D and AH:	g at the propulation of the prop	erty location descring of the company of the caused by the flood proofing being the caused by the flood to prevent of the caused by the flood floo	puilding at the proposed and the average of the elevation of the development of the elevation of the development of the elevation of the eleva	perty location described above the highest adjacent grade new meer or Architect) the building is watertight, with ability of resisting hydrostatives velocities, impact and upleman intervention? to the base flood level octubeling metal shields over the actual lowest floor must be monis feet, (NGVD LICENSE NO. (or Affix Seal)

INSURANCE AGENTS MAY ORDER THIS FORM REPLACES FEMA FORMS 81-9(T) AND 81-10(T). FEB 80. WHICH ARE OBSOLETE,