

FEDERAL EMERGENCY MANAGEMENT AGENCY

OMB 3067-0077 Expires: June 1984

ION CERTIFICATE

This form is to be used for: 1) New/Emergency Program construction in Special Flood Hazard Areas; 2) Pre-FIRM construction after September 30, 1982; 3) Post-FIRM construction; and, 4) Other buildings rated as Post-FIRM rules.

BUILDING OWNER'S NAME

Russell & Virginia Rongren

Lot 8							
atement may be punis	hable by fine	cation (Com	ent under 18	U.S. code, Section cal Community Pe	n 1001.		derstand that any false Professional Engineer,
OMMUNITY NO. PANEL N	O. SUFFIX	DATE OF FIRM	FIRM ZONE	DATE OF CONSTR	BASE FLOOD E (In AO Zone, use	LEV. BUILI depth)	DING IS ☐ New/Emergency ☐ Pre-FIRM Reg. ☐ Post-FIRM Reg.
□ □ ordinance. of	The certifier ft, NGVD	may rely on co	mmunity rec	ords. The lowest luilding at this elev	loor (including I	pasement) v	nunity's flood plain will be at an elevation g in violation of
□ □ ordinance t	ased on elev	ation data and	visual inspec	in compliance w ction or other read the community.		ty's flood pl	lain management
YES NO The mobile	home locate	d at the address	ss described a	above has been ti in compliance wi	ed down (ancho th the NFIP Spe	red) in com cifications.	pliance with the
MOBILE HOME M		MODEL		OF MANUFACTU		RIAL NO.	DIMENSIONS X
Community Permit O	ficial or Reg	stered Profess	ional Enginee	er, Architect, or S	urveyor)		
NAME		*.		ADDRESS			
TITLE		CITY			STATE		ZIP
	We Daniel	(18)		DATE	BHON	-	
SIGNATURE				DATE	PHON		d Professional Enginee
	at an elevation	t the building a ion of +15 of +14.00	feet, NGVD	y location describ VD (mean sea le	vel) and the ave	the bottom	at the building site is a
FIRM ZONES V, V1-V	at an elevation an elevation (30: I certify at an e is at an elevation). Hand EMER feet,	t the building a ion of +15 of +14.00 that the building levation of elevation of NGVD. The elevation of the building at the satisfactory of the sa	the property loca	y location describ VD (mean sea let) perty location described, NGVD (mean seet, NGVD.	cribed above has a level), and the the property log grade next to the lower has the lo	the bottom a average gradien describuilding is _	of the lowest floor bear rade at the building sit ibed above has the lowe feet, NGV
FIRM ZONES V, V1-V FIRM ZONES A, A99, A floor elevation of FIRM ZONE AO: I cer feet, NGVD. The eleva	at an elevat an elevation 30: I certify at an e is at an H and EMER feet, ify that the b	the building a ion of +15 of +14.00 that the building levation of elevation of NGVD. The elevation ghest adjacent	the propert 07 feet, NGVD ng at the prop feet feet RAM: I certify evation of the property loca grade next to	y location describ VD (mean sea let) perty location described, NGVD (mean seet, NGVD.	oribed above has a level), and the level, and the level the property lograde next to the lower has the lower ferman and the lower has the lower ferman and t	the bottom a average gradient describuilding is _ est floor ele et, NGVD.	as ferrors with
FIRM ZONES V, V1-V FIRM ZONES A, A99, A loor elevation of EIRM ZONE AO: I cer eet, NGVD. The eleva SECTION III FLOOD I certify to the best of walls substantially im and hydrodynamic loi	at an elevat an elevation 30: I certify at an e is at an H and EMER feet, ify that the b tion of the hi PROOFING I my knowle permeable to ds and effect the base flo In the even	the building a ion of +15 of +14.00 that the building levation of elevation of NGVD. The elevation of the passage of the passa	the property NGVD feet, NGVD feet, NGVD feet, NGVD feet, NGVD feet, NGVD feet, NGVD feet feet feet feet feet feet feet fee	y location describ VD (mean sea let) Derty location described, NGVD (mean seat, NGVD. I that the building a highest adjacent of the building is the building is that the building structural compose caused by the e of floodproofing will enter the building will enter the	oribed above has a level), and the level), and the level), and the level the property lograde next to the lower has the lower fed Professional is designed so nents having the flood depths, professional depths, professional level with flood depths, professional depths, professional level with flood depths, professional level with flood depths, professional depths, professional level with flood depths, professional level with flood depths, professional level with flood depths, professional level	the bottom average grade cation describuilding is_ est floor eleet, NGVD. Engineer o that the bu e capability essures veleth human in	of the lowest floor bear rade at the building sit ibed above has the lowe feet, NGV vation of r Architect) ilding is watertight, wil of resisting hydrostat ocities, Impact and upli
FIRM ZONES A, A99, A loor elevation of	at an elevat an elevation 30: I certify at an e is at an H and EMER feet, lify that the b tion of the hi PROOFING I my knowle- permeable to de and effect the base flo In the even (Human int Cur unless doors and Will the bu	the building a ion of +15 to 1	the propert O.7 feet, NGVD feet,	y location describ VD (mean sea let) Derty location described, NGVD (mean seet, NGVD. That the building a highest adjacent of the building is particular to the building structural compose caused by the e of floodproofing will enter the building the flood to prevent dence?	oribed above has a level), and the are the property loor grade next to the over has the lowered Professional is designed so nents having the flood depths, property look achieved with ding when flood ent entry of water rating purposes	the bottom a average grade cation descr building is _ est floor ele et, NGVD. Engineer o that the bu e capability essures velo th human in s up to the r (e.g., bolti	at the building site is a of the lowest floor bear rade at the building sit ibed above has the lowe feet, NGV vation of r Architect) ilding is watertight, wil of resisting hydrostat ocities, impact and upli itervention? base flood level oc-
FIRM ZONES A, A99, A loor elevation of	at an elevat an elevation 30: I certify at an e is at an H and EMER feet, ify that the b tion of the hi PROOFING I my knowle permeable to dots and effect the base flo In the even (Human int cur unless doors and Will the bu questions is to	the building a ion of +15 of +14.00 that the building levation of elevation of selevation of NGVD. The elevation of the passage of the passa	the propert O.7 feet, NGVD feet,	y location describ VD (mean sea let) Derty location described, NGVD (mean seat, NGVD. Ithat the building a highest adjacent of tion described aboothe building is— attion by a Registe that the building structural compose caused by the e of floodproofing will enter the built the flood to prevent dence? ot be credited for and floodproofing	oribed above has a level), and the are the property loor grade next to the over has the lowered Professional is designed so nents having the flood depths, property look achieved with ding when flood ent entry of water rating purposes	the bottom a average grade cation descr building is _ est floor ele et, NGVD. Engineer o that the bu e capability essures velo th human in s up to the r (e.g., bolti and the aci	of the lowest floor bear rade at the building sit ibed above has the lowe feet, NGV vation of r Architect) iilding is watertight, wi of resisting hydrostat ocities, Impact and upl stervention? base flood level oc- ing metal shields over
FIRM ZONES V, V1-V FIRM ZONES A, A99, A loor elevation of FIRM ZONE AO: I cer- eet, NGVD. The eleva SECTION III FLOOD certify to the best o walls substantially im and hydrodynamic loo lorces associated with YES NO YES NO If the answer to both completed and certific FIRM ZONES A, A1,-A	at an elevat an elevation 30: I certify at an e is at an H and EMER feet, lify that the b tion of the hi PROOFING I my knowle- permeable to the base flo In the even (Human int cur unless doors and Will the bu questions is 1 d instead. C. 330, V1-V30, 7	the building a ion of +15 of +14.00 that the building levation of elevation of gency PROG NGVD. The elevation of the passage	the propert O.7 feet, NGVD feet, NGVD feet, NGVD feet, NGVD feet, NGVD feet, NGVD feet feet feet feet feet feet feet fee	y location describ VD (mean sea let) VD (mean sea let) Derty location described, NGVD (mean seet, NGVD. That the building a highest adjacent of the building is particular to the building structural compose caused by the electron of the described to prevent the flood to prevent the flood to prevent the control of the credited for and floodproofing Certified	oribed above has a level), and the average and	the bottom average grade cation describuilding is est floor eleet, NGVD. Engineer o that the buse capability essures velocity the thore of the capability essures velocity and the accidental support of the capability essures velocity and the accidental support of the capability essures velocity essures velocity and the accidental support of the capability essures velocity	at the building site is a of the lowest floor bear rade at the building sit ibed above has the lowe feet, NGV vation of r Architect) ilding is watertight, wi of resisting hydrostat ocities, impact and upl atervention? base flood level oc- ing metal shields over tual lowest floor must if
FIRM ZONES V, V1-V FIRM ZONES A, A99, A loor elevation of FIRM ZONE AO: I cereet, NGVD. The eleva SECTION III FLOOD Certify to the best of walls substantially im and hydrodynamic loor lorces associated with YES NO YES NO If the answer to both completed and certifice FIRM ZONES A, A1,-A THIS CERTIFICATION CERTIFICATION CERTIFICATION CERTIFICATION	at an elevation an elevation an elevation an elevation at an e is at an e is at an e is at an elevation and elevation of the him elevation of the him elevation and effect the base flowed and effect the base flowed and effect unless doors and will the buquestions is a dinstead. Co. 30, V1-V30, VIS FOR Elevations	the building a ion of +15 to 1 +14 to 1 +15 to 1 +14 to 1 that the building at the part of the passage of the p	the propert OT feet, NGVD feet, NGVD feet, NGVD feet, NGVD feet, NGVD feet, NGVD feet feet feet feet feet feet feet fee	y location describ VD (mean sea let) VD (mean sea let) Derty location desc, NGVD (mean seat, NGVD. Ithat the building a highest adjacent of the building is seat that the building is structural compose caused by the e of floodproofing will enter the building the flood to prevent the flood to prevent the credited for and floodproofing Certified CCTIONS II AND II	cribed above has a level), and the are the property lograde next to the over has the lower feet and professional is designed so nents having the flood depths, professional depths, professional are the professional is designed so nents having the flood depths, professional depths, professional is designed so nents having the flood depths, professional depths are the flood depths are th	the bottom average grade cation describuilding is est floor eleet, NGVD. Engineer o that the buse capability essures velocity the thore of the capability essures velocity and the accidental support of the capability essures velocity and the accidental support of the capability essures velocity essures velocity and the accidental support of the capability essures velocity	of the lowest floor bearade at the building site is a carde at the building site is a carde at the building site ibed above has the lowed feet, NGV vation of feet, NGV vation of feet, NGV vation of resisting hydrostat ocities, impact and uple tervention? base flood level ocing metal shields over tual lowest floor must feet, (NGVI)
FIRM ZONES V, V1-V FIRM ZONES A, A99, A loor elevation of FIRM ZONE AO: I cer- eet, NGVD. The eleva SECTION III FLOOD I certify to the best or walls substantially im and hydrodynamic loo forces associated with YES □ NO □ YES □ NO □ If the answer to both completed and certifie FIRM ZONES A, A1,-A THIS CERTIFICATIO CERTIFIER'S NAME Raymo	at an elevation an elevation an elevation an elevation at an e is at an e is at an e is at an elevation and elevation of the him elevation of the him elevation and effect the base flowed and effect the base flowed and effect unless doors and will the buquestions is a dinstead. Co. 30, V1-V30, VIS FOR Elevations	the building a ion of +15 of +14.00 that the building levation of elevation of gency PROG NGVD. The elevation of the passage	the propert OT feet, NGVD feet, NGVD feet, NGVD feet, NGVD feet, NGVD feet, NGVD feet feet feet feet feet feet feet fee	y location describ VD (mean sea let) Derty location described. Described in the building a highest adjacent of the building is personal to the building is personal to the building structural compose caused by the electron of the building will enter the building will ent	cribed above has a level), and the are the property lograde next to the over has the lower feet and professional is designed so nents having the flood depths, professional depths, professional are the professional is designed so nents having the flood depths, professional depths, professional is designed so nents having the flood depths, professional depths are the flood depths are th	the bottom average grade cation describuilding is est floor eleet, NGVD. Engineer o that the buse capability essures velocity the thore of the capability essures velocity and the accidental support of the capability essures velocity and the accidental support of the capability essures velocity essures velocity and the accidental support of the capability essures velocity	at the building site is a of the lowest floor bear rade at the building sit ibed above has the lowe feet, NGV vation of r Architect) ilding is watertight, wi of resisting hydrostat ocities, impact and upl atervention? base flood level oc- ing metal shields over tual lowest floor must if
FIRM ZONES V, V1-V FIRM ZONES A, A99, A Ploor elevation of	at an elevation an elevation an elevation an elevation at an e is at an e is at an e is at an elevation and elevation of the him elevation of the him elevation and effect the base flowed and effect the base flowed and effect unless doors and will the buquestions is a dinstead. Co. 30, V1-V30, VIS FOR Elevations	the building a ion of +15 to 1 +14 to 1 +15 to 1 +14 to 1 that the building at the part of the passage of the p	the propert OT feet, NGVD feet fe	y location describ VD (mean sea let) Derty location described. Described in the building a highest adjacent of the building is personal to the building is personal to the building structural compose caused by the electron of the building will enter the building will ent	cribed above has a level), and the stribed above has a level), and the stribed above has the lower over has the lowered Professional is designed so nents having the flood depths, professional action of the stribed action	the bottom average grade cation describuilding is est floor eleet, NGVD. Engineer o that the buse capability essures velocity the thore of the capability essures velocity and the accidental support of the capability essures velocity and the accidental support of the capability essures velocity essures velocity and the accidental support of the capability essures velocity	of the lowest floor bear rade at the building site is a libed above has the lowe feet, NGV vation of feet, NGV vation of resisting hydrostation of resisting hydrostation of resisting hydrostation of resisting hydrostation in tervention? base flood level octing metal shields over tual lowest floor must be feet, (NGVE)
FIRM ZONES V, V1-V FIRM ZONES A, A99, A floor elevation of FIRM ZONE AO: I cert feet, NGVD. The eleva SECTION III FLOOD I certify to the best o walls substantially im and hydrodynamic los forces associated with YES NO If the answer to both completed and certific FIRM ZONES A, A1,-A THIS CERTIFICATION CERTIFIER'S NAME Raymo TITLE Press SIGNATURE	at an elevat an elevation an elevation of 1 certify at an e is at an elevation of the him of the base flowed and effect the base flowed and effect the base flowed and effect the base flowed and elevations and the work of the him of the even of the him of the even of the him	the building a ion of +15 of +14.00 that the building levation of elevation of elevation of Sency PROG NGVD. The elevation of the passage of	the propert O.7 feet, NGVD feet,	y location described by location described. Derty location described by location described about the building is lation by a Register at the building structural compose caused by the location described about the flood proofing will enter the building structural compose caused by the location described for location described for the flood to prevent dence? Out the credited for and floodproofing Certified CCTIONS II AND ITY NAME Am Survey S hamrock B	ribed above has a level), and the average above has a level), and the average are at the property logarized next to the pove has the lower of the property logarized next to the pove has the lower of the property logarized next to the pove has the lower of the property logarized next having the flood depths, property logarized next property of water at the property logarized next property	the bottom average grade the bottom average grade cation describuilding is set floor elect, NGVD. Engineer of that the buse capability essures velocity and the action of the control of	of the lowest floor bear rade at the building site is a state of the lowest floor bear rade at the building site ibed above has the lowed feet, NGV vation of feet, NGV vation of resisting hydrostate