OMB 3067-0077 Expires: Feb. 1987



NATIONAL FLOOD INSURANCE PROGRAM

This form is to be used for: 1) New/Emergency Program construction in Special Flood Hazard Areas; 2) Pre-FIRM construction after September 30, 1982; 3) Post-FIRM construction; and, 4) Other buildings rated as Post-FIRM rules.

| ILDING OW | | | | | | | | | | |
|--|--|--|--|--|--|--|---|--|--|--|
| ME | NER'S | | | | ADDRESS | | 6878 | | | |
| NA STATE OF THE PARTY OF THE PA | | | | | | | | | | |
| OPERTY LO | CATION (L | ot and Blo | ock numbers a | nd address if | available) | | | | | |
| t 3, 7 | 1.75. C. | Form | min Ton | o linit | 7 Boxes | י מליניםי | Jande ' | ٦ -1. | 1'alram | ic 35 |
| ertify that th tement may | e information be punisha | on on this ble by fine | certificate rep or imprisonm | resents my b ent under 18 | est efforts to interp U.S. code, Section | pret the dat n 1001. | ta available. | Lunderst | and that ar | ly talse |
| | | | CATION (Com | | cal Community Pe | | ıl or a Regis | tered Profe | essional En | gineer, |
| MMUNITY NO | PANEL NO. | SUFFIX | DATE OF FIRM | FIRM ZONE | DATE OF CONSTR. | | OOD ELEV. e, use depth) | BUILDING I | | |
| .5144 | 0239 | D | 5-1-04 | 1-12 | Ame. 107 | 77 | | | ☐ New/Em ☐ Pre-FIR ☐ Post-FI | M Reg |
| S NO It is | s intended t linance. The | e certifier ft, NGVD | ilding describe | ed above will emmunity reconstruct the b | be constructed in ords. The lowest fl uilding at this elev | loor (includ | ding basem | ent) will be | at an ele | ration |
| □ ord | linance bas | ed on elev | ation data and | visual inspe | d in compliance will ction or other reas to the community. | | | od plain m | nanagemer | nt |
| S NO The | e mobile ho | me locate | d at the addre | ss described ordinance, or | above has been tie in compliance wit | ed down (a | nchored) in | complian | ce with the | • |
| | HOME MAK | | MODEL | | OF MANUFACTU | | SERIAL | | DIMENSI | ONS |
| | | A.100 | | | | | | | . × | |
| | No. 10 (5 (1) | | | 1 | as Asabitant 0 | I I I I I I I I I I I I I I I I I I I | | | * 1. 5. | |
| 8.5 | rermit Offici | ial or Regi | stered Profess | ional Engine | er, Architect, or Su | nveyor) | | - 10 | | |
| ME | | | | | ADDRESS | | | - 6- | * | |
| TLE | | | CITY | - 100E | | STAT | ΓE | | ZIP | - |
| GNATURE | | | 1. | | DATE | P | HONE | · · | | A |
| RM ZONE | at | an elevat | t the building | the proper | ty location describe | ed above h | as the lowe | st floor (in | cluding ba | sement) |
| T. | at ar | an elevation elevation elevation | t the building a ion of that the buildilevation of | the proper feet, NGVI | rveyor.) ty location describ- GVD (mean sea levo). perty location describ- t, NGVD (mean se | ed above h | as the lowe a average g | st floor (in rade at the | cluding ba e building | sement) site is at |
| 4 | at ar | an elevation elevation elevation : I certify at an e | t the building ion of | the proper feet, NGVI | rveyor.) ty location describ- SVD (mean sea lev). perty location desc | ed above h | as the lowe a average g | st floor (in rade at the | cluding ba e building | sement) site is at |
| RM ZONES | at ar | an elevation elevation elevation in elevation in elevation in elevation in elevation in elevation elevatio | the building a ion of that the buildi levauon of elevation of services of the | the properior feet, NGVI | rveyor.) ty location describ- GVD (mean sea levo). perty location describ- t, NGVD (mean se | ed above he vel) and the cribed above a level), and the cribed above a level), are | as the lowe e average g e has the bo d the avera | st floor (in rade at the ttom of the ge grade | e lowest float the build | sement) site is at or beam ding site |
| RM ZONES | A, A99, AH | an elevation ele | the building a ion of that the building at the | the property local | ty location describ GVD (mean sea lev D. perly location desc t, NGVD (mean se set, NGVD. | ed above help and the cribed above a level), are the properade next to ove has the | e has the board the average of the building to the building to the building to the building to the building towest floor | st floor (in rade at the standard floor of the ge grade described g is | ecluding base building a lowest float the building | sement) site is at or beam ding site |
| RM ZONES RM ZONES por elevation IRM ZONE A ret, NGVD. T | A, A99, AH | an elevation elevation elevation elevation: I certify at an e is at an e is at an end EMER feet, that the bin of the hi | the building a ion of that the buildi levauon of elevation of NGVD. The elevation gat the ghest adjacent | the property local grade next to | ty location described to location described about 15 l | ed above help and the cribed above a level), are the properade next to ove has the | e has the bod the avera | st floor (innrade at the | e lowest float the building | sement) site is at or beam ding site |
| RM ZONES RM ZONES por elevation RM ZONE A et, NGVD. T ECTION III certify to the alls substant nd hydrodyr proces associa | A, A99, AH: AO: I certify he elevation FLOODPF he best of mainic loads ated with th | an elevation I certify at an e is at an elevation I certify at an e is at an end EMER feet, that the bin of the him elevation of thim elevation of the him elevation of the him elevation of the him | the building a ion of that the buildi levation of elevation of elevation of NGVD. The elevation general discontinuity of the passage of the passage of buoyance of the passage of the pass | at the property feet, NGVI grade next in Cortific on, and belief of water and y that would | ty location described by that the building as thighest adjacent gation described about the building is attion by a Register f, that the building is structural composite by the | ed above herel) and the cribed above a level), and the cribed above a level), are the cribed above has the cred Profess is designed and the cribed above herel by the cribed above herel profess is designed above herel by the cribed above herel by the cr | e has the bod the average of the building the cape in | st floor (intrade at the state of the ge grade described gis or elevation VD. deer or Arcue buildings billity of reserved in sevelocities | above has feet of the building above has feet of the building above has feet of the building is waterties is the building is waterties in pact in pact in the building is waterties. | or beam ding site he loweslet, NGVD |
| RM ZONES RM ZONES por elevation IRM ZONE A ret, NGVD. T ECTION III certify to the valls substant nd hydrodyr proces associa | A, A99, AH: AO: I certify The elevation FLOODPF tie best of mittally impernamic loads ated with th NO [] In (() | an elevation elevation elevation elevation: I certify at an e is at an elevation elev | the building a ion of that the buildi levation of elevation of elevation of NGVD. The elevation general department of the passage its of buoyanc od. | the property local grade next look (Certific on, and believed that would will this degree on that water and y that water on the property local grade of the | ty location described to mean sea levol. perty location described. perty location described, NGVD (mean sea levol.) y that the building a highest adjacent goation described about the building is ation by a Register f, that the building is structural composite the structural composite in the sea levol. | ed above help and the cribed above a level), and the cribed above a level), are the properties over has the cred Profess is designed in the cred profess is designed to be achieved ding when | e has the bod the average grant location of the building feet, NG | st floor (intrade at the state of the ge grade described g is | above has feed at the building is waterties is feed at the feed at the building is waterties at the feed | or beam ding site he lowest at, NGVD. |
| RM ZONES RM ZONES or elevation RM ZONE A et, NGVD. T ECTION III certify to the alls substant d hydrodyr rces associatives YES YES YES | A, A99, AH: AO: I certify he elevation FLOODPF The best of manic loads ated with th NO I I I I I I I I I I I I I I I I I I I | an elevation I certify at an e is at an elevation I certify at an e is at an end EMER feet, that the bin of the him eleventh el | the building a ion of that the building a ion of that the building at the ghest adjacent depending at the ghest adjacent depending at the ghest adjacent depending at the passage at the passage at the passage are windows). | at the property feet, NGVI grade next in Cortific on, and belief of water and y that water taken prior to pied as a resi | ty location described by that the building as highest adjacent gation described about the building is attion by a Register f, that the building is structural compose caused by the ee of floodproofing will enter the build the flood to prevent the property of the flood to prevent dence? | ed above here!) and the cribed above a level), are the proper grade next to the profess is designed and the cred profess is designed and the credit profess is designed and the credit profess is designed and the credit profess in the credit pr | e has the bod the average gray location of the building location of the building locational Engined so that the gray the capaths, pressured with hum floods up to water (e.g. | st floor (intrade at the state of the ge grade of the ge grade of the ge grade of the ge grade of the state o | above has labove has l | or beam ding site is at or beam ding site is at or beam ding site is at or beam ding site is own ding site is over is sover is at the site is over it |
| RM ZONES or elevation RM ZONE A et, NGVD. T ECTION III Certify to the alls substant d hydrodyr rces associa YES YES the answer | A, A99, AH: AO: I certify he elevation FLOODPF he best of mitially imperamic loads ated with the NO I li | an elevation is at an elevation elevation is at an elevation is at an elevation is at an elevation of the him of the him of the him of the him elevation is an elevation is at an elevat | the building a ion of that the building a ion of that the building a that the building at the ghest adjacent certain day, information the passage at of buoyanc od. It of flooding, we revention mea measures are windows). | at the property feet, NCV feet, NGVI feet, N | ty location described to the building a structural compose caused by the ce of floodproofing will enter the building to the flood to prevent the building as a building as a building as a building is at the building is at t | ed above here!) and the cribed above a level), are the proper and enext to the profess is designed and the cred profess is designed and the credity of the profess is designed and the credity of the credity o | e has the bod the average gray location to the building the capaths, pressure and with hum floods up to water (e.g. | st floor (intrade at the state of the ge grade of the ge grade of the ge grade of the ge grade of the state o | above has labove has l | or beam ding site is at or beam ding site is at or beam ding site is at or beam ding site is own ding site is over is sover is at the site is over it |
| RM ZONES RM ZONES FOR elevation RM ZONE A Let, NGVD. T ECTION III Certify to the alls substant d hydrodyr rces associa YES the answer completed an | A, A99, AH in of | an elevation elevation elevation elevation elevation elevation. I certify at an e is at an elevation elev | the building a ion of that the buildi levation of elevation of elevation of NGVD. The elevation of the ghest adjacent of the passage at sof buoyanc od. It of flooding, were windows). Ilding be occurred, the flooding be occurred, the flooding be occurred, the flooding of the passage at sof buoyanc od. | at the property feet, NCV feet, NGVI feet, N | perty location described by location described by location described by location described. NGVD (mean sevent, NGVD) The perty location described above the building a bighest adjacent go ation described above to the building is attroctural composible caused by the sevent location of the flood proofing will enter the building the flood to prevent dence? | ed above help and the cribed above a level), and the cribed above a level), are the properties over has the cred Profess is designements having flood deptile be achieved ding when ent entry of certificates | e has the bod the average gray location to the building the capaths, pressure and with hum floods up to water (e.g. | described described gis described at the described of the general state of the described of the described of the building of the building of the base, bolting of the base, bolting of the described of the base, bolting of the described of the base, bolting of the described of the base, bolting of the base, bolting of the base, bolting of the described of the base, bolting of the described of the | above has labove has l | or beam ding site is at or beam ding site is at or beam ding site is at or beam ding site is own ding site is over is sover is at the instance of the instance |
| RM ZONES RM ZONES or elevation RM ZONE A et, NGVD. T ECTION III certify to the alls substand hydrodyr rices associately YES the answer minimum zones IRM ZONES | A, A99, AH: AO: I certify he elevation FLOODPF he best of matic loads ated with the NO | an elevation elevation elevation elevation elevation : I certify at an e is at an elevation elev | the building a ion of that the building a ion of that the building at the ghest adjacent of the passage its of buoyanc od. It of flooding, where the passage its of buoyanc od. It of flooding, where the passage is of buoyanc od. It of flooding, where the passage is of buoyanc od. It of flooding, where the passage is of buoyanc od. It of flooding, where the passage is of buoyanc od. It of flooding, where the passage is of buoyanc od. It of flooding is occurred to the passage is of buoyanc od. It of flooding is occurred to the passage is of buoyanc od. It of flooding be occurred to the passage is of buoyanc od. It of flooding be occurred to the passage is of buoyanc od. | at the property feet, NGVI feet, | perty location described by location described by location described by location described. NGVD (mean sevent, NGVD) The perty location described above the building a bighest adjacent go ation described above to the building is attroctural composible caused by the sevent location of the flood proofing will enter the building the flood to prevent dence? | ed above he vel) and the vel) and the vel) and the vel) and the vel), are the properties of the properties of the velocity of the properties of the velocity of the properties of the velocity | e has the bod the average gray location to the building the capaths, pressure and with hum floods up to water (e.g. | described described gis described at the described of the general state of the described of the described of the building of the building of the base, bolting of the base, bolting of the described of the base, bolting of the described of the base, bolting of the described of the base, bolting of the base, bolting of the base, bolting of the described of the base, bolting of the described of the | above has labove has l | or beam ding site with a lowest at, NGVD. ght, with a drostatic and uplift is over |
| RM ZONES RM ZONES BOT elevation RM ZONE A et, NGVD. T ECTION III certify to the alls substand d hydrodyr rices associa YES the answer ompleted ar IRM ZONES HIS CERTIF | A, A99, AH: AO: I certify he elevation FLOODPF The best of manic loads ated with the NO II is Control of the certified in | an elevation elevation elevation elevation elevation : I certify at an e is at an elevation elev | the building a ion of that the building a ion of that the building at the ghest adjacent of the passage its of buoyanc od. It of flooding, where the passage its of buoyanc od. It of flooding, where the passage is of buoyanc od. It of flooding, where the passage is of buoyanc od. It of flooding, where the passage is of buoyanc od. It of flooding, where the passage is of buoyanc od. It of flooding, where the passage is of buoyanc od. It of flooding is occurred to the passage is of buoyanc od. It of flooding is occurred to the passage is of buoyanc od. It of flooding be occurred to the passage is of buoyanc od. It of flooding be occurred to the passage is of buoyanc od. | at the property feet, NGVI grade next in the property local grade | ty location described by location described about the building a shighest adjacent gration described about the building is attion by a Register f, that the building is structural composible caused by the see of floodproofing will enter the building the flood to prevent of the credited for and floodproofing. | ed above he vel) and the vel) and the vel) and the vel) and the vel), are the properties of the properties of the velocity of the properties of the velocity of the properties of the velocity | e has the bod the average gray location to the building the capaths, pressure and with hum floods up to water (e.g. | described described gis described at the described of the general state of the described of the described of the building of the building of the base, bolting of the base, bolting of the described of the base, bolting of the described of the base, bolting of the described of the base, bolting of the base, bolting of the base, bolting of the described of the base, bolting of the described of the | above has labove has l | or beam ding site is at or beam ding site is at or beam ding site is at or beam ding site is over it is over it must be |
| RM ZONES RM ZONES POR JONES RM ZONES RM ZONE A et, NGVD. T ECTION III certify to the alls substanding hydrodyring associative associative and hydrodyring and hydrodyring associative and hydrodyring associative and hydro | A, A99, AH in of AO: I certify the elevation FLOODPF the best of mathematic loads atted with the NO II in the both quent of the both quent of the best of the both quent of th | an elevation elevation elevation elevation: I certify at an e is at an end EMER feet, that the bin of the him end effect end before and effect end end effect elevations and effect elevations in the even distributed by the bin end effect elevations in the even elevations and effect elevations in the even elevations in the elevations in the elevation elevations in the elevations in the elevation elevation elevation elevations in the elevation | the building a ion of that the building a ion of that the building at the ghest adjacent of the passage its of buoyanc od. It of flooding, where the passage its of buoyanc od. It of flooding, where the passage is of buoyanc od. It of flooding, where the passage is of buoyanc od. It of flooding, where the passage is of buoyanc od. It of flooding, where the passage is of buoyanc od. It of flooding, where the passage is of buoyanc od. It of flooding is occurred to the passage is of buoyanc od. It of flooding is occurred to the passage is of buoyanc od. It of flooding be occurred to the passage is of buoyanc od. It of flooding be occurred to the passage is of buoyanc od. | the property feet, NC grade next for water and y that would will this degree ns that water aken prior to pied as a resion of fine elevation. | ty location described by location described about the building a structural component of the flood proofing will enter the building the flood to prevent described for and floodproofing location described by the locat | ed above he vel) and the vel) and the vel) and the vel) and the vel), are the properties of the properties of the velocity of the properties of the velocity of the properties of the velocity | e has the bod the average gray location to the building the capaths, pressure and with hum floods up to water (e.g. | described described gis described at the described of the general state of the described of the described of the building of the building of the base, bolting of the base, bolting of the described of the describ | above has labove has l | or beam ding site with a lowest at, NGVD. ght, with a drostatic and uplift is over |
| RM ZONES RM ZONES RM ZONES RM ZONES RM ZONE A Ret, NGVD. T ECTION III Certify to the ralls substant and hydrodyr cress associates YES If the answer completed are RM ZONES HIS CERTIFIER'S CITLE | A, A99, AH in of AO: I certify the elevation of the best of manic loads ated with the NO II in the both que did certified in AO: I certify the best of manic loads ated with the NO II in the both que did certified in AO: I in the both que did certified in AO: I in NAME | an elevation elevation elevation elevation elevation elevation. I certify at an e is at an elevation elev | the building a ion of that the building at the glevation of elevation of elevation of NGVD. The elevation of the ghest adjacent of the passage its of buoyanc od. It of flooding, we therefore the flooding between the control of the passage is of buoyanc od. It of flooding, we therefore the flooding between the flooding betw | the property feet, NC grade next is grade next in the property local grade next in the property loc | perty location described by location described about the building a strict by a Register of the building structural composite caused by the location described about the building structural composite caused by the location described by l | ed above help and the proper and ext to ove has the profess is designents having flood deption of the entry of the extrement | e has the bod the average gray location to the building the capaths, pressure and with hum floods up to water (e.g. | described described gis described at the described of the general state of the described of the described of the building of the building of the base, bolting of the base, bolting of the described of the describ | above has labove has l | or beam ding site with a lowest at, NGVD. ght, with a drostatic and uplift is over |
| RM ZONES RM ZONES RM ZONES RM ZONES RM ZONE A Ret, NGVD. T ECTION III Certify to the ralls substant and hydrodyr cress associates YES If the answer completed are RM ZONES HIS CERTIFIER'S CITLE | A, A99, AH in of AO: I certify the elevation of the best of manic loads ated with the NO II in the both que did certified in AO: I certify the best of manic loads ated with the NO II in the both que did certified in AO: I in the both que did certified in AO: I in NAME | an elevation elevation elevation elevation elevation elevation. I certify at an e is at an elevation elev | the building a ion of that the building a ion of that the buildi levation of elevation of elevation of NGVD. The elevation of the ghest adjacent of the passage its of buoyanc od. It of flooding, where the passage is of buoyanc od. It of flooding with the passage its of buoyanc od. It of flooding with the passage its of buoyanc od. It of flooding with the passage its of buoyanc od. It of flooding with the passage its of buoyanc od. It of flooding with the passage its of buoyanc od. It of flooding with the passage its of buoyanc od. It of flooding with the passage its of buoyanc od. It of flooding with the passage its of buoyanc od. | the property feet, NC grade next in the property local grade next | perty location described by location described about the building at highest adjacent gration described about the building is pation by a Register for the building is structural composite caused by the gration described by the gration described by the caused by the gration described by the gration described for and floodproofing will enter the building the flood to prevent the flood to prevent dence? The control of the credited for and floodproofing certified by NAME The control of the control of the credited for and floodproofing certified by NAME The control of the c | ed above help and the proper and ext to ove has the profess is designents having flood deption of the entry of the extrement | e has the bod the average get | described described gis described at the described of the general state of the described of the described of the building of the building of the base, bolting of the base, bolting of the described of the describ | above has labove has l | or beam ding site is at or beam ding site is at or beam ding site is at or beam ding site is over it is over it must be |
| IRM ZONES IRM ZONES oor elevation IRM ZONE A tet, NGVD. T ECTION III certify to the total substant of th | A, A99, AH: AO: I certify he elevation FLOODPF The best of milally imperamic loads atted with the NO II (CO NO NO II (CO NO NO NO NO NO NO NO NO NO | an elevation elevation elevation elevation elevation elevation. I certify at an e is at an elevation elev | the building a ion of that the building at the glevation of elevation of elevation of NGVD. The elevation of the ghest adjacent of the passage its of buoyanc od. It of flooding, we therefore the flooding between the control of the passage is of buoyanc od. It of flooding, we therefore the flooding between the flooding betw | the property feet, NC grade next in the property local grade next | perty location described by location described about the building a strict by a Register of the building structural composite caused by the location described about the building structural composite caused by the location described by l | ed above he vel) and the vel) and the vel) and the vel) and the vel), are the properties of the properties of the velocity of the properties of the velocity o | e has the bod the average gray location to the building the capaths, pressure and with hum floods up to water (e.g. | described described gis described at the described of the general state of the described of the described of the building of the building of the base, bolting of the base, bolting of the described of the describ | above has labove has l | ght, with drostatic and uplift is seal (NGVD) |