9NO3163

ELEVATION CERTIFICATE

O.M.B. No. 3067-007 Expires July 31, 1999

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information neoessary to ensure compliance with applicable community floodplain management ordinances, to determine proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). You are no quired to respond to this collection of information unless a valid OMB control number is displayed in the upper right corner of this form. Received tons for completing this form can be found on the following pages. Construction From A PROPERTY INFORMATION FCR INSURANCE COMPANY USE Dept. POLICY NUMBER BUILDING OWNER'S NAME 1999 LEONARD E. LEETZOW, JR Received STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER COMPANY NAIC NUMBER Construction & Property Stds OTHER DESCRIPTION (Lot and Block Numbers, etc.) SECTION BAYWOOD STATE ZIP CODE SRIDA SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION Provide the following from the proper FIRM (See Instructions): 1. COMMUNITY NUMBER 2. PANEL NUMBER 3. SUFFIX 4. DATE OF FIRM INDEX 5. FIRM ZONE 6. BASE FLOOD ELEVATION (in AO Zones, use depth) SEPT. 3,1992 ΑE 125144 0143 EL. 12.0 7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): NGVD '29 Cther (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: I I I I feet NGVD (or other FIRM datum-see Section B, Item 7) SECTION C BUILDING ELEVATION INFORMATION sing the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best escribes the subject building's reference level 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of 1118.2 feet NGVD (or other FIRM datum-see Section B, Item 7). SEE COMMENTS (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of 1111 feet NGVD (or other FiRM datum-see Section B, Item 7). (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is ______ feet above ___ or below (check one) the highest grade adjacent to the building. (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is feet above or below (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? Yes No Unknown 3. Indicate the elevation datum system used in determining the above reference level elevations: X NGVD '29 🗌 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.) 4. Elevation reference mark used appears on FIRM: Tyes X No (See Instructions on Page 4) 5. The reference level elevation is based on: X actual construction L construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.) 6. The elevation of the lowest grade immediately adjacent to the building is: _______ feet NGVD (or other FIRM datum-see Section B, Item 7). SECTION D COMMUNITY INFORMATION 1. If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: [| | | | | | | | feet NGVD (or other FIRM datum-see Section B. Item 7).

2. Date of the start of construction or substantial improvement

9NO3163

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.


Reference level diagrams 6, 7 and 8 - Distinguishing Features—If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

- Andrew		7 3	194	*			# £ 24	
J.B.1	BURCH ETT			LICENSE NUMB	ER (or Affix Seal)			1,
TITLE			COMPANY					
	EY MANA	her	ME	A GROU	PIINOC.	14		
ADDRESS 5071	ATTLERID	55 B.	CITY		,		STATE	ZIP.
SIGNATURE	- 0	and the same of th	10.	ARA SO		FL	RIDA	3423
	13 Burch	rett		7/23/99	9 (O41	342-	-6321
Copies should	d be made of this Ce	rtificate for: 1)	community off	icial, 2) insurance	agent/comp	any, and 3) building o	wner.
COMMENTS:	GARAGE	FINIS	4 FLOC	R EL	8.2	_		
- 840	ENTRY	FINISH	FLOC	R EL.	12.0			
	LIVING	FINISH	1 FLOO	or El	12,0)		

Not To Be Rename

SARASOTA COUNTY



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.