

# NOTICE OF PRODUCT CERTIFICATION



**Company:** Masonite International Corporation  
 1955 Powis Road  
 West Chicago, IL 60185

**Certification No.:** NI013747.01-R4  
**Certification Date:** 06/08/2017  
**Expiration Date:** 06/30/2027  
**Revision Date:** 11/14/2023

**Product:** Wood-Edge Steel Full-Lite Glazed Inswing or Outswing Door w/Non-Impact Rated Sidelites  
 (Requires "HPC" Construction Slabs) (w/Wood Frame unless noted)

**Specification:** TAS 202-94/ASTM E330-02/14/M-14

**Glazing:** Insulating Glass (Tempered)

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit [www.namicertification.com](http://www.namicertification.com). NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Structural Design Pressure	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S	Glazed	3'0" x 6'8"	+50/-50	0.0 psf	No	NCTL-110-19469-6/W-1961/W-2094 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0212-17
X Single	O/S	Glazed	3'0" x 6'8"	+50/-50	3.0 psf <sup>1</sup> 4.5 psf <sup>2</sup> 7.50 psf <sup>3,4,5</sup>	No	NCTL-110-19469-6/W-1857/W-1961/W-2094 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0212-17
XX Double	I/S	Glazed	6'0" x 6'8"	+50/-50	0 psf	No	NCTL-110-19469-6/W-1961/W-2094 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0212-17
XX Double	O/S	Glazed	6'0" x 6'8"	+50/-50	3.0 psf <sup>1</sup> 4.5 psf <sup>2</sup> 7.50 psf <sup>3</sup>	No	NCTL-110-19469-6/W-1961/W-2094 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0212-17
XO/OX Single w/Sidelite	I/S	Glazed	6'0" x 6'8"	+50/-50	0 psf	Door-No Sidelite-No	NCTL-110-19469-6/W-1961/W-2094 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0212-17
XO/OX Single w/Sidelite	O/S	Glazed	6'0" x 6'8"	+50/-50	3.0 psf <sup>1</sup> 4.5 psf <sup>2</sup> 7.50 psf <sup>3</sup>	Door-No Sidelite-No	NCTL-110-19469-6/W-1961/W-2094 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0212-17
OXO Single w/Sidelites	I/S	Glazed	9'0" x 6'8"	+50/-50	0 psf	Door-No Sidelite-No	NCTL-110-19469-6/W-1961/W-2094 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0212-17
OXO Single w/Sidelites	O/S	Glazed	9'0" x 6'8"	+50/-50	3.0 psf <sup>1</sup> 4.5 psf <sup>2</sup> 7.50 psf <sup>3</sup>	Door-No Sidelite-No	NCTL-110-19469-6/W-1961/W-2094 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0212-17
OXXO Double w/Sidelites	I/S	Glazed	12'4" x 6'8"	+50/-50	0 psf	Door-No Sidelite-No	NCTL-110-19469-6/W-1961/W-2094 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0212-17
OXXO Double w/Sidelites	O/S	Glazed	12'4" x 6'8"	+50/-50	3.0 psf <sup>1</sup> 4.5 psf <sup>2</sup> 7.50 psf <sup>3</sup>	Door-No Sidelite-No	NCTL-110-19469-6/W-1961/W-2094 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0212-17

1 -Denotes Bumper Outswing Threshold 2 -Denotes Z-Series Outswing Threshold 3-Hi-Dam Outswing Threshold 4-Pro T4 Threshold 5-HP Outswing Threshold

**National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072**

**Tel: (804) 684-5124/nami@namiinc.com**

**NAMI AUTHORIZED SIGNATURE:** \_\_\_\_\_ *ShD*